

# Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and  
GHS





Printing date 21.06.2013

Revision: 21.06.2013

## 1 Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier** IBS No. 10929
- **Trade name:** Bead Sealer
- **Article number:** 14-101, 14-104, 14-101A, 14-101B, 14-104A, 14-104B
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**  
No further relevant information available.
- **Application of the substance / the preparation** Sealant
- **1.3 Details of the supplier of the Safety Data Sheet**
- **Manufacturer/Supplier:**  
31 Incorporated  
100 Enterprise Dr.  
Newcomerstown, OH 43832  
Phone: (740) 498-8324
- **1.4 Emergency telephone number:**  
ChemTel Inc.  
(800)255-3924, +1 (813)248-0585

## 2 Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**  
The following Hazard Statements are applicable only to the general GHS regulations and not the specific CLP regulation: H361.  
The following Hazard Statements are applicable only to the EU regulations and not the US GHS regulation: H361d, H400, H410.
-  H361: Suspected of damaging fertility or the unborn child.
-  GHS02 flame  
 Flam. Liq. 2      H225    Highly flammable liquid and vapour.
-  GHS08 health hazard  
 Repr. 2            H361d   Suspected of damaging the unborn child.  
 STOT RE 2        H373    May cause damage to organs through prolonged or repeated exposure.
-  GHS09 environment  
 Aquatic Acute 1    H400   Very toxic to aquatic life.  
 Aquatic Chronic 1 H410   Very toxic to aquatic life with long lasting effects.

(Contd. on page 2)

# Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and  
GHS

Printing date 21.06.2013

Revision: 21.06.2013

Trade name: **Bead Sealer**

(Contd. of page 1)



GHS07

Skin Irrit. 2      H315    Causes skin irritation.  
 Skin Sens. 1B    H317    May cause an allergic skin reaction.  
 STOT SE 3        H336    May cause drowsiness or dizziness.

· **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**

Xn; Harmful

R48/20-63:    Harmful: danger of serious damage to health by prolonged exposure through inhalation.  
 Possible risk of harm to the unborn child.

Xi; Irritant

R38:            Irritating to skin.

Xi; Sensitising

R43:            May cause sensitisation by skin contact.

F; Highly flammable

R11:            Highly flammable.

N; Dangerous for the environment

R50/53:        Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R67:            Vapours may cause drowsiness and dizziness.

· **Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

· **Classification system:**

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

The classification is in accordance with the latest editions of international substances lists, and is supplemented by information from technical literature and by information provided by the company.

· **2.2 Label elements**

· **Labelling according to Regulation (EC) No 1272/2008**

The following Hazard Statements are applicable only to the EU regulations and not the US GHS regulation: H410.

The product is classified and labelled according to the CLP regulation.

(Contd. on page 3)

# Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and  
GHS

Printing date 21.06.2013

Revision: 21.06.2013

Trade name: **Bead Sealer**

(Contd. of page 2)

- **Hazard pictograms**



This pictogram only applicable for EU regulations. Not for use in the United States (OSHA GHS).



GHS02 GHS07 GHS08 GHS09

- **Signal word** Danger

- **Hazard-determining components of labelling:**

toluene

Natural rubber latex

- **Hazard statements**

The following Hazard Statements are applicable only to the general GHS regulations and not the specific CLP regulation: H361.

H361: Suspected of damaging fertility or the unborn child. (General GHS and USA only)

The following Hazard Statements are applicable only to the EU regulations and not the US GHS regulation: H361d, H410.

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H361d Suspected of damaging the unborn child.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H410 Very toxic to aquatic life with long lasting effects.

- **Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P281 Use personal protective equipment as required.

P233 Keep container tightly closed.

P260 Do not breathe mist/vapours/spray.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P314 Get medical advice/attention if you feel unwell.

P370+P378 In case of fire: Use for extinction: CO<sub>2</sub>, powder or water spray.

P403+P235 Store in a well-ventilated place. Keep cool.

- **Hazard description:**

- **WHMIS-symbols:**

B2 - Flammable liquid

D2A - Very toxic material causing other toxic effects



(Contd. on page 4)

# Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and  
GHS

Printing date 21.06.2013

Revision: 21.06.2013

Trade name: **Bead Sealer**

(Contd. of page 3)

· **NFPA ratings (scale 0 - 4)**

Health = 2  
Fire = 3  
Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**

HEALTH **2** Health = \*2  
FIRE **3** Fire = 3  
REACTIVITY **0** Reactivity = 0

\* - Indicates a long term health hazard from repeated or prolonged exposures.

· **HMIS Long Term Health Hazard Substances**

108-88-3 | toluene

· **2.3 Other hazards**· **Results of PBT and vPvB assessment**· **PBT:** Not applicable.· **vPvB:** Not applicable.

## 3 Composition/information on ingredients

· **3.2 Mixtures**· **Description:** Mixture of substances listed below with nonhazardous additions.· **Dangerous components:**

CAS: 108-88-3 EINECS: 203-625-9 Index number: 601-021-00-3	toluene Xn R48/20-63-65;  Xi R38;  F R11 R67 Repr. Cat. 3 ----- Flam. Liq. 2, H225 Repr. 2, H361d; STOT RE 2, H373; Asp. Tox. 1, H304 Skin Irrit. 2, H315; STOT SE 3, H336	50-100%
CAS: 142-82-5 EINECS: 205-563-8 Index number: 601-008-00-2	heptane Xn R65;  Xi R38;  F R11;  N R50/53 R67 ----- Flam. Liq. 2, H225 Asp. Tox. 1, H304 Aquatic Acute 1, H400; Aquatic Chronic 1, H410 Skin Irrit. 2, H315; STOT SE 3, H336	25-50%
CAS: 9006-04-6	Natural rubber latex Xi R43 ----- Skin Sens. 1B, H317	<10%

· **Additional information:** For the wording of the listed risk phrases refer to section 16.

(Contd. on page 5)

# Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and  
GHS

Printing date 21.06.2013

Revision: 21.06.2013

Trade name: **Bead Sealer**

(Contd. of page 4)

## 4 First aid measures

### · 4.1 Description of first aid measures

#### · **General information:**

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Take affected persons out into the fresh air.

· **After inhalation:** Supply fresh air; consult doctor in case of complaints.

#### · **After skin contact:**

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

#### · **After eye contact:**

Remove contact lenses if worn.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

#### · **After swallowing:**

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; call for medical help immediately.

### · 4.2 Most important symptoms and effects, both acute and delayed

Dizziness

Headache

Coughing

Cramp

Nausea

Disorientation

Allergic reactions

### · **Hazards**

Danger of cerebral oedema.

Danger of convulsion.

Danger of disturbed cardiac rhythm.

Condition may deteriorate with alcohol consumption.

### · 4.3 Indication of any immediate medical attention and special treatment needed

If swallowed, gastric irrigation with added, activated carbon.

Monitor circulation, possible shock treatment.

If necessary oxygen respiration treatment.

Medical supervision for at least 48 hours.

Later observation for pneumonia and pulmonary oedema.

Treat skin and mucous membrane with antihistamine and corticoid preparations.

## 5 Firefighting measures

### · 5.1 Extinguishing media

#### · **Suitable extinguishing agents:**

Foam

Alcohol resistant foam

Fire-extinguishing powder

Carbon dioxide

(Contd. on page 6)

# Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and  
GHS

Printing date 21.06.2013

Revision: 21.06.2013

**Trade name: Bead Sealer**

(Contd. of page 5)

- Gaseous extinguishing agents
- Water haze or fog
- CO<sub>2</sub>, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:**
- Water spray
- Water with full jet
- **5.2 Special hazards arising from the substance or mixture**
- Formation of toxic gases is possible during heating or in case of fire.
- **5.3 Advice for firefighters**
- **Protective equipment:**
- Wear self-contained respiratory protective device.
- Wear fully protective suit.
- **Additional information**
- Eliminate all ignition sources if safe to do so.
- Use large quantities of foam as it is partially destroyed by the product.
- Cool endangered receptacles with water fog or haze.

## 6 Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
- Use respiratory protective device against the effects of fumes/dust/aerosol.
- Wear protective equipment. Keep unprotected persons away.
- Ensure adequate ventilation
- Keep away from ignition sources.
- Protect from heat.
- **6.2 Environmental precautions:**
- Do not allow product to reach sewage system or any water course.
- Inform respective authorities in case of seepage into water course or sewage system.
- Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
- Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- Allow to solidify. Pick up mechanically.
- Send for recovery or disposal in suitable receptacles.
- Dispose contaminated material as waste according to item 13.
- Ensure adequate ventilation.
- Do not flush with water or aqueous cleansing agents
- **6.4 Reference to other sections**
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

## 7 Handling and storage

- **7.1 Precautions for safe handling**
- Keep receptacles tightly sealed.
- Keep away from heat and direct sunlight.

(Contd. on page 7)

# Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and  
GHS

Printing date 21.06.2013

Revision: 21.06.2013

**Trade name: Bead Sealer**

(Contd. of page 6)

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· **Information about fire - and explosion protection:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

· **7.2 Conditions for safe storage, including any incompatibilities**

· **Storage:**

· **Requirements to be met by storerooms and receptacles:**

Store in a cool location.

Provide ventilation for receptacles.

Avoid storage near extreme heat, ignition sources or open flame.

· **Information about storage in one common storage facility:**

Store away from foodstuffs.

Store away from oxidizing agents.

· **Further information about storage conditions:**

Store in cool, dry conditions in well sealed receptacles.

Keep container tightly sealed.

· **7.3 Specific end use(s)** No further relevant information available.

## 8 Exposure controls/personal protection

· **Additional information about design of technical facilities:** No further data; see item 7.

· **8.1 Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

**108-88-3 toluene**

PEL (USA) Short-term value: C 300; 500\* ppm

Long-term value: 200 ppm

\*10-min peak per 8-hr shift

REL (USA) Short-term value: 560 mg/m<sup>3</sup>, 150 ppm

Long-term value: 375 mg/m<sup>3</sup>, 100 ppm

TLV (USA) Long-term value: 75 mg/m<sup>3</sup>, 20 ppm

BEI

EL (Canada) Long-term value: 20 ppm

R

EV (Canada) Long-term value: 20 ppm

**142-82-5 heptane**

IOELV (EU) Long-term value: 2085 mg/m<sup>3</sup>, 500 ppm

PEL (USA) Long-term value: 2000 mg/m<sup>3</sup>, 500 ppm

REL (USA) Short-term value: C 1800\* mg/m<sup>3</sup>, C 440\* ppm

Long-term value: 350 mg/m<sup>3</sup>, 85 ppm

\*15-min

(Contd. on page 8)

## Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and  
GHS

Printing date 21.06.2013

Revision: 21.06.2013

<b>Trade name: Bead Sealer</b>
--------------------------------

(Contd. of page 7)

TLV (USA)	Short-term value: 2050 mg/m <sup>3</sup> , 500 ppm Long-term value: 1640 mg/m <sup>3</sup> , 400 ppm
EL (Canada)	Short-term value: 500 ppm Long-term value: 400 ppm
EV (Canada)	Short-term value: 2,045 mg/m <sup>3</sup> , 500 ppm Long-term value: 1,635 mg/m <sup>3</sup> , 400 ppm

### 9006-04-6 Natural rubber latex

TLV (USA)	Long-term value: 0,0001* mg/m <sup>3</sup> Skin; (SEN) NIC-DSEN, RSEN;* inh. fraction
EL (Canada)	Long-term value: 0,001 mg/m <sup>3</sup> inhalable, Skin; S
EV (Canada)	Long-term value: 0,001 mg/m <sup>3</sup> as total proteins, inhalable, Skin

- **DNELs** No further relevant information available.
- **PNECs** No further relevant information available.

### · Ingredients with biological limit values:

#### 108-88-3 toluene

BEI (USA)	0,02 mg/L Medium: blood Time: prior to last shift of workweek Parameter: Toluene
	0,03 mg/L Medium: urine Time: end of shift Parameter: Toluene
	0,3 mg/g creatinine Medium: urine Time: end of shift Parameter: o-Cresol with hydrolysis (background)

- **Additional information:** The lists valid during the making were used as basis.

### · 8.2 Exposure controls

#### · Personal protective equipment:

#### · General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

#### · Respiratory protection:

For spills, respiratory protection may be advisable.

Use suitable respiratory protective device in case of insufficient ventilation.

Use suitable respiratory protective device when aerosol or mist is formed.

(Contd. on page 9)



# Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and  
GHS

Printing date 21.06.2013

Revision: 21.06.2013

Trade name: **Bead Sealer**

(Contd. of page 8)

- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation.

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **For the permanent contact gloves made of the following materials are suitable:**

Fluorocarbon rubber (Viton)

PVA gloves

- **Eye protection:**



Safety glasses

- **Body protection:** Protective work clothing

- **Limitation and supervision of exposure into the environment**

No further relevant information available.

- **Risk management measures**

See Section 7 for additional information.

No further relevant information available.

## 9 Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

· <b>Form:</b>	Liquid
· <b>Colour:</b>	Black
· <b>Odour:</b>	Solvent-like
· <b>Odour threshold:</b>	Not determined.

· **pH-value:** Not determined.

- **Change in condition**

· **Melting point/Melting range:** Undetermined.

(Contd. on page 10)

## Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and  
GHS

Printing date 21.06.2013

Revision: 21.06.2013

Trade name: **Bead Sealer**

(Contd. of page 9)

<b>Boiling point/Boiling range:</b>	210 ° F / 99 ° C
· <b>Flash point:</b>	16 ° F / -9 ° C (TCC D56)
· <b>Flammability (solid, gaseous):</b>	Not applicable.
· <b>Ignition temperature:</b>	419 ° F/215 ° C
· <b>Decomposition temperature:</b>	Not determined.
· <b>Self-igniting:</b>	Product is not self-igniting.
· <b>Danger of explosion:</b>	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· <b>Explosion limits:</b>	
<b>Lower:</b>	1,1 Vol %
<b>Upper:</b>	7,0 Vol %
· <b>Vapour pressure at 20 °C:</b>	48 hPa
· <b>Density at 20 °C:</b>	0,87 g/cm <sup>3</sup>
· <b>Relative density</b>	Not determined.
· <b>Vapour density</b>	Not determined.
· <b>Evaporation rate</b>	Not determined.
· <b>Solubility in / Miscibility with water:</b>	Not miscible or difficult to mix.
· <b>Partition coefficient (n-octanol/water):</b>	Not determined.
· <b>Viscosity:</b>	
<b>Dynamic:</b>	Not determined.
<b>Kinematic at 20 °C:</b>	721 mm <sup>2</sup> /s (Converted from 5 Zahn)
· <b>Solvent content:</b>	
<b>VOC (California)</b>	75-90 % Wt
· <b>9.2 Other information</b>	No further relevant information available.

### 10 Stability and reactivity

- **10.1 Reactivity**
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used and stored according to specifications.
- **10.3 Possibility of hazardous reactions**  
Can react violently with oxygen rich (oxidizing) material. Danger of Explosion.  
Used empty containers may contain product gases which form explosive mixtures with air.  
Reacts with reducing agents.  
Flammable.  
Reacts with oxidizing agents.  
Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomised.

(Contd. on page 11)

# Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and  
GHS

Printing date 21.06.2013

Revision: 21.06.2013

Trade name: **Bead Sealer**

(Contd. of page 10)

Toxic fumes may be released if heated above the decomposition point.

- **10.4 Conditions to avoid**

Keep ignition sources away - Do not smoke.

Store away from oxidizing agents.

- **10.5 Incompatible materials:** No further relevant information available.

- **10.6 Hazardous decomposition products:**

Carbon dioxide

Carbon monoxide

Danger of forming toxic pyrolysis products.

## 11 Toxicological information

- **11.1 Information on toxicological effects**

- **Acute toxicity:**

- **LD/LC50 values relevant for classification:**

**108-88-3 toluene**

Oral	LD50	5000 mg/kg (rat)
Dermal	LD50	12124 mg/kg (rabbit)
Inhalative	LC50/4 h	5320 mg/l (mouse)

**142-82-5 heptane**

Oral	LD50	> 5000 mg/kg (rat) (Estimate)
Inhalative	LC50/4 h	103 mg/l (rat)

**1333-86-4 Carbon black**

Oral	LD50	10000 mg/kg (rat)
------	------	-------------------

- **Primary irritant effect:**

- **on the skin:** Irritant to skin and mucous membranes.

- **on the eye:** Slight irritant effect on eyes.

- **Sensitization:** Sensitization possible through skin contact.

- **Additional toxicological information:**

Inhalation of concentrated vapours as well as oral intake will lead to anaesthesia-like conditions and headache, dizziness, etc.

Toxic and/or corrosive effects may be delayed up to 24 hours.

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Irritant

Danger through skin adsorption.

- **Repeated dose toxicity:**

May cause damage to organs through prolonged or repeated exposure .

Repeated exposures may result in skin and/or respiratory sensitivity.

- **CMR effects (carcinogenity, mutagenicity and toxicity for reproduction):**

Repr. 2

(Contd. on page 12)

# Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and  
GHS

Printing date 21.06.2013

Revision: 21.06.2013

Trade name: **Bead Sealer**

(Contd. of page 11)

## 12 Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** Toxic for aquatic organisms
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:**  
Very toxic for fish  
Due to mechanical actions of the product (e.g. agglutinations) damages may occur.  
The product is oxygen-consuming. The declared action may be partly caused by lack of oxygen.
- **Additional ecological information:**
- **General notes:**  
This statement was deduced from the properties of the single components.  
Avoid transfer into the environment.  
Due to available data on eliminability/decomposition and bioaccumulation potential prolonged term damage of the environment can not be excluded.  
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water  
Do not allow product to reach ground water, water course or sewage system.  
Danger to drinking water if even small quantities leak into the ground.  
Also poisonous for fish and plankton in water bodies.  
Very toxic for aquatic organisms
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

## 13 Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**  
Can be reused after reprocessing.  
Contact waste processors for recycling information.  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.  
Can be burned with household garbage after consulting with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

## 14 Transport information

- **14.1 UN-Number**
- **DOT, ADR, IMDG, IATA** UN1993

(Contd. on page 13)

## Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and  
GHS

Printing date 21.06.2013

Revision: 21.06.2013

Trade name: **Bead Sealer**

(Contd. of page 12)

· **14.2 UN proper shipping name**  
 · DOT  
 · ADR  
 · IMDG  
 · IATA

Flammable liquids, n.o.s.  
 1993 FLAMMABLE LIQUID, N.O.S. (TOLUENE,  
 HEPTANES), ENVIRONMENTALLY HAZARDOUS  
 FLAMMABLE LIQUID, N.O.S. (TOLUENE,  
 HEPTANES), MARINE POLLUTANT  
 FLAMMABLE LIQUID, N.O.S. (TOLUENE,  
 HEPTANES)

· **14.3 Transport hazard class(es)**

· DOT


 · Class  
 · Label

 3 Flammable liquids.  
 3

· ADR


 · Class  
 · Label

 3 (F1) Flammable liquids.  
 3

· IMDG


 · Class  
 · Label

 3 Flammable liquids.  
 3

· IATA


 · Class  
 · Label

 3 Flammable liquids.  
 3
· **14.4 Packing group**

· DOT, ADR, IMDG, IATA

III

· **14.5 Environmental hazards:**

Product contains environmentally hazardous substances: heptane

· **Marine pollutant:**
 Yes  
 Symbol (fish and tree)

(Contd. on page 14)

## Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and  
GHS

Printing date 21.06.2013

Revision: 21.06.2013

Trade name: **Bead Sealer**

(Contd. of page 13)

· <b>Special marking (ADR):</b>	Symbol (fish and tree)
· <b>14.6 Special precautions for user</b>	Warning: Flammable liquids.
· <b>Danger code (Kemler):</b>	33
· <b>EMS Number:</b>	F-E, S-E
· <b>14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b>	Not applicable.
· <b>Transport/Additional information:</b>	
· <b>ADR</b>	
· <b>Limited quantities (LQ)</b>	5L
· <b>Transport category</b>	3
· <b>Tunnel restriction code</b>	D/E
· <b>UN "Model Regulation":</b>	UN1993, FLAMMABLE LIQUID, N.O.S. (TOLUENE, HEPTANES), ENVIRONMENTALLY HAZARDOUS, 3, III

### 15 Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **United States (USA)**
- **SARA**

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

108-88-3 | toluene

· **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

· **Proposition 65 (California):**

· **Chemicals known to cause cancer:**

References to chemical components listed below are based on unbound respirable particles and are not generally applicable to product as supplied.

1333-86-4 | Carbon black

· **Chemicals known to cause reproductive toxicity for females:**

108-88-3 | toluene

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

108-88-3 | toluene

(Contd. on page 15)

# Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and  
GHS

Printing date 21.06.2013

Revision: 21.06.2013

Trade name: **Bead Sealer**

(Contd. of page 14)

- **Carcinogenic Categories**

- **EPA (Environmental Protection Agency)**

108-88-3	toluene	II
142-82-5	heptane	D

- **IARC (International Agency for Research on Cancer)**

108-88-3	toluene	3
1333-86-4	Carbon black	2B

- **TLV (Threshold Limit Value established by ACGIH)**

108-88-3	toluene	A4
1333-86-4	Carbon black	A4

- **NIOSH-Ca (National Institute for Occupational Safety and Health)**

1333-86-4	Carbon black	
-----------	--------------	--

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

- **Canada**

- **Canadian Domestic Substances List (DSL)**

All ingredients are listed.

- **Canadian Ingredient Disclosure list (limit 0.1%)**

None of the ingredients is listed.

- **Canadian Ingredient Disclosure list (limit 1%)**

108-88-3	toluene	
142-82-5	heptane	

- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**

- H225 Highly flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H336 May cause drowsiness or dizziness.
- H361d Suspected of damaging the unborn child.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- R11 Highly flammable.
- R38 Irritating to skin.
- R43 May cause sensitisation by skin contact.

(Contd. on page 16)

# Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and  
GHS

Printing date 21.06.2013

Revision: 21.06.2013

**Trade name: Bead Sealer**

(Contd. of page 15)

R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.

R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R63 Possible risk of harm to the unborn child.

R65 Harmful: may cause lung damage if swallowed.

R67 Vapours may cause drowsiness and dizziness.

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

WHMIS: Workplace Hazardous Materials Information System (Canada)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

· **Sources**

SDS Prepared by:

ChemTel Inc.

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: [www.chemtelinc.com](http://www.chemtelinc.com)