

LOCTITE

YOUR CHOICE BUY 2, GET 1 1/2 PRICE!



NEW!

Loctite 5699™ Gray RTV

IBS No. 40505 190ml

Loctite® RTV Gray Silicone Gasket Maker Power Cans replace most any cut gasket. Designed specifically for high performance applications, RTV Gray makes reliable formed-in-place gaskets that resist cracking, shrinking and migrating.

- Can also be used to coat gaskets and increase reliability.
- Temperature range of -75° to 625°.
- Resists auto and shop fluids, and is not corrosive.
- One part RTV silicone that remains flexible and withstands high vibration.
- Designed for high-torque applications.
- Non-corrosive, low odor, tack-free after 10 minutes.
- Water-glycol resistant.
- Ideal for use on flexible flanges, machined or cast surfaces, metal or plastic.
- Power Can dispenser uses an innovative adhesive system designed to make application easy — a built-in lever that controls the flow of silicone, allowing the user to extrude precise amounts of product with the press of a finger.

IDEAL FOR SEALING

Valve Covers • Oil Pans • Water Pumps
Thermostat Housings • Transmission Parts

Loctite 515™ Purple Gasket Eliminator

IBS No. 51531 50ml

NEW!



LOCTITE® 515 is a medium strength, medium cure speed, methacrylate-based industrial gasketing product designed for machined, rigid metal flanges. The product, which cures anaerobically, is suitable for gaps up to 0.25mm. It is used typically as a form-in-place product for pumps, thermostats, compressors, transmission housings and axle covers.

Loctite® Gasket Maker 515™ Flange Sealant is a flexible, gasketing material for use on rigid machined flanges with less than 0.25mm gap. OEM approved. Eliminates preformed, pre-cut, paper, rubber and cork gaskets.

Recommended for use on rigid iron, steel and aluminum flanges e.g. aluminum gearbox and engine castings, etc. Easy disassembly and cleaning.

- Ideal for machined metal components
- Perfect seal between components
- For gaps up to 0.25mm
- 30 min fixture time.

LOCTITE - BUY 2, GET 1 - 1/2 PRICE



3rd item must be of
equal or lesser value!