MATERIAL SAFETY DATA SHEET

Product Name: Buffing Solution

Page 1 of 4

SEG	CTION 1 -	PRODUCT AND C	OMPANY		ICATION		
PRODUCT NAME: PART NUMBER(S): GENERAL USE: PRODUCT DESCRIPTION:	14-100 for preparing t	ution IBS No. 10928 the tire innerliner to receive a	a tire repair		X seal		
MANUFACTURER'S NAME: 31 Incorporated STREET ADDRESS: 100 Enterprise Drive CITY, STATE, ZIP, COUNTRY Newcomerstown, OH 43832 U	Group Incorporated		DATE PREPARED: June 7, 2011 SUPERSEDES: Jan 1, 2010 FOR INFORMATION, CONTACT: (740) 498-8324; info@31inc.com EMERGENCY TELEPHONE NUMBER: CHEM • TEL: (800) 255-3924 or (813) 248-0585				
SECTION 2 - HAZARDOUS INGREDIENTS							
HAZARDOUS COMPONENTS	%	CAS #	TLV UNITS	Hazard Symbol	RISK PHRASES (Full Text Section 16)		
HEXANE HEPTANES ACETONE	35 - 45 35 - 45 10 - 20	110-54-3 142-82-5 67-64-1					
	SEC	TION 3 - HAZARD			1		
EMERGENCY OVERVIEW Contact with eyes will cause irri ACCUTE EFFECTS OF OVEREXI	tation. Contac						
Inhalation:	May cause dizziness						
Skin:	May cause irri	tation upon prolonged or rep	peated contact				
Eyes:	Eyes: May cause irritation, redness, tearing						
Ingestion:	May cause irritation of gastrointestinal tract.						
CHRONIC EFFECTS OF OVEREX	KPOSURE:						
N/A							
OTHER HEALTH HAZARDS: N/A							
	SI	ECTION 4 - FIRST	AID MEAS	SURES			
INHALATION:	Give oxygen						
SKIN:	Wash with soa	ap and large quantities of wa	ater. If irritation	persists, seek	medical attention.		
EYES:	Flush with larg	ge quantities of clean water	for at least 15 m	ninutes. Seek r	nedical attention.		
INGESTION:	Do NOT give a	anything by mouth or induce	vomiting. See	k immediate m	edical attention.		

MATERIAL SAFETY DATA SHEET Product Name: Buffing Solution

Page 2 of 4

SECTION 5 - FIRE FIGHTING MEASURES								
EXTINGUISHING MEDIA:	Foam, CO_2 , Dry Chemical, F			AUUNEC	•			
	10011, 002, Dry Olicinical, 1		pparatus					
FIRE FIGHTING PROCEDURES:	FIGHTING PROCEDURES: Use of self contained breathing apparatus is recommended for fire fighters							
UNUSUAL FIRE AND	Extremely flammable and ma	av he ignited h	wheat snarks	flame or othe	er source of igni	ition		
EXPLOSION HAZARDS:	Extremely flammable and may be ignited by heat, sparks, flame, or other source of ignition. Closed containers can explode due to buildup of pressure when exposed to extreme heat.							
	SECTION 6 - ACCI		RELEAS	E MEASL	IRES			
STEPS TO BE TAKEN IN CASE M COMBUSTIBLE - Evacuate and into approved absorbent; place regulations; Do NOT wash to s	d ventilate area; remove all so material into approved conta	ources of spar iners for dispo	osal following al	I Local, State,	and Federal	bsorb		
	SECTION 7 - I	HANDLIN	IG AND S	TORAGE				
PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: This material is combustible. It should be stored in tightly closed containers in a cool, well ventilated area. Vapors may form explosive mixtures in air. All sources of ignition should be controlled. Keep this and other chemicals out of reach of children. Avoid inhaling concentrated fumes or vapors.								
SECTIC	SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION							
HAZARDOUS COMPONENTS	NIO	SH			ACC	ЭIН		
HAZARDOUS COMPONENTS	TWA ppm TWA mg/m3	STEL ppm	STEL mg/m3	TWA ppm	TWA mg/m3	STEL ppm	STEL mg/m3	
ACETONE								
PERSONAL PROTECTION:								
Respiratory Protection:	Use NIOSH approved cartridge or gas mask. Refer to 29 CFR 1910.134 or European Standard EN 149 for complete regulations.							
Ventilation:	Mechanical ventilation to keep product within specified TLV ranges.							
Protective Gloves:	Imperable gloves advised.							
Eye Protection:	Protective eyeglasses or chemical safety goggles. Refer to 29 CFR 1910.133 or European Standard EN 166.							
Other:	Work clothes							
Work / Hygienic Practices: Practice safe workplace habits. Minimize body contact with this product.								
SE	CTION 9 - PHYSIC	AL AND	CHEMIC	L PROP	ERTIES			
APPEARANCE AND ODOR:			VAPOR PRES	SURE AT 20°	°C:			
Liquid, clear Solvent-like			N/A					
BOILING POINT / RANGE: 180 F / 82.2C			SPECIFIC GR	AVITY:				
FREEZING POINT:			SOLUBILITY I	N WATER (%	by weight):			
FLASH POINT (Test Methods):			very slight V.O.C.:					
-15C / 9F TCC			90%-					
				VAPOR DENSITY: Heavier than air				
EVAPORATION RATE:								
faster than butyl acetate								

MATERIAL SAFETY DATA SHEET

Product Name: Buffing Solution

Page 3 of 4

SECTION 10 - STABILITY AND REACTIVITY							
STABILITY:	UNSTABLE: STABLE:	XXX	CONDITIONS TO AVOID	: Heat, Flames, sparks			
INCOMPATIBILITY (Materials to Avoid): Strong oxydizers							
HAZARDOUS COMBUSTION or DECOMPOSITION PRODUCTS:	CO or CO2						
HAZARDOUS POLYMERIZATION:	MAY OCCUR: WILL NOT OCCUR:	XXX	CONDITIONS TO AVOID	: N/A			
SECTION 11 - TOXICOLOGICAL INFORMATION							
HAZARDOUS COMPONENTS	CAS # EINECS #	(Specif	O OF INGREDIENT y Species and Route)	LC50 OF INGREDIENT (Specify Species)			
HEXANE	110-54-3	ora dern					
		inha	lation 171.6mg rat				
HEPTANE							
ACETONE							
	SECTION 12 - E						
No data are available on the advers				available.			
Based on the chemical composition	of this product, it is assumed	I that the mixt	ure can be treated in an acclimatiz	ed biological waste			
treatment plant system in limited qu				h specific			
biological system. None of the ingredients in this mixture are classified as a Marine Pollutant.							
Do not allow to enter drains, water courses or the soil.							
SECTION 13 - DISPOSAL CONSIDERATIONS							
WASTE DISPOSAL METHOD: Dispose of in accordance with Local, State, and Federal Regulations. This product may produce							
hazardous vapors or fumes in a closed disposal container creating a dangerous environment. Refer to "40 CFR Protection of Environment Parts 260 - 299" for complete waste disposal regulations. Consult your local, state, or federal Environmental							
				Uninental			
Protection Agency (EPA) before disposing of any chemicals. Do NOT flush to sanitary sewer or waterway.							
SECTION 14 - TRANSPORT INFORMATION							
PROPER SHIP	PING NAME: Petroluem Dist	illates NOS					
DOT HAZARD CLASS / Pack Group: 3 PG II			IATA HAZARD CLASS/Pack Group: 3 PG II				
REFERENCE:				CLASS: 3 PG II			
UN / NA IDENTIFICATIO		RID/ADR Dangerous Good					
LABEL: FLAMMABLE UN TDG Class / Pack Group:							
HAZARD SYMBOLS: Note: Transportation information if for reference only. Client is urged to consult CFR 49 parts 100 - 177, IMDG, IATA, EU,							
United Nations TDG, and WHMIS (Canada) TDG information manuals for detailed regulations and exceptions covering specific							
container sizes, packaging materials, and methods of shipping.							

MATERIAL SAFETY DATA SHEET Product Name: Buffing Solution

Page 4 of 4

SECT	ION 15 - REGU	LATORY INFO	RMATION			
TSCA (USA - Toxic Substance Control Act) All components of this product are listed on t from listing because a Low Volume Exemtpic	ne U.S. Toxic Substance	Control Act Chemical	Inventory (TSCA Inventory) or are	e exempted		
SARA TITTLE III (USA - Superfund Amendment 311/312 Hazard Categories: Immediate health	s and Reauthorization A	ct)				
313 Reportable Ingredients: None						
CERCLA (USA - Comprehensive Response Cor None	npensation and Liability	Act)				
CPR (Canadian Controlled Products Regulation This product has been classified in accordan all the information required by the Controlled	ce with the hazard criteri	a of the Controlled Pro	ducts Regulations and the MSDS	contains		
IDL (Canadian Ingredient Disclosure List) Components of this product identified by CAS	S number are listed on th	e Canadian Ingredient	Disclosure List are shown in Sec	tion 2.		
DSL / NDSL (Canadian domestic Substances Li Components of this product identified by CAS document. Only ingredients classified as "ha	S number are listed on th	e DSL or NDSL and m		2 of this		
EINECS (European Inventory of Existing Comm Components of this product identified by CAS			isting Commercial Chemical Sub	stances.		
RISK PHRASES:	SYMBOL(S) REQUIRE	ED FOR LABEL:	SAFETY PHRASES:			
R36/38 Irritating to eyes and skin	Flammable FLAMMABLE LIQUID	Irritan	t S2 Keep out of re S41 In case of fire do not breathe	and/or explosion		
S	ECTION 16 - OT	HER INFORM	ATION			
NOTES & FULL R-PHRASE TEXT: R36/38 Irritating to eyes and skin						
HMIS HAZARD RATINGS:	HEALTH 2					
F	LAMMABILITY 3					
REACTIVITY 0 PERSONAL PROTECTIVE EQUIPMENT A						
REVISION SUMMARY:						
MSDS PREPARED BY: Paul Clark / 31 Incorpore	ted					
100 Enterprise Dr. Newcomerstown, OH 43832 740-498-8324 pclark@31inc.com						
The information contained herein is based on da				g the		
accuracy of this data or the results to be obtained				r third		
persons proximately caused by the materials if r Additionally, vendor assumes no responsibility for				aterial		
even if reasonable safety procedures are followed						