## SAFETY DATA SHEET

1. Identification

Product number 74173

Product identifier 14 OZ ENVIRO-SEAL PARTS PROTECTOR

Company information IBS Inc.

PO Box 1717

AUBURN, WA 98071-1717

Company phone General Assistance 253-804-8666

**Emergency telephone US** 1-800-255-3924 **Emergency telephone outside** 1-813-248-0573

US

Version # 09
Recommended use Coating
Recommended restrictions None known.

2. Hazard(s) identification

Physical hazardsFlammable aerosolsCategory 1Health hazardsGerm cell mutagenicityCategory 1B

Carcinogenicity Category 1B Specific target organ toxicity, repeated Category 1

exposure

Aspiration hazard Category 1

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Danger

**Hazard statement** Extremely flammable aerosol. May be fatal if swallowed and enters airways. May cause genetic defects. May cause cancer. Causes damage to organs through prolonged or repeated exposure.

**Precautionary statement** 

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe gas. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/protective clothing/eye protection/face protection.

Response If swallowed: Immediately call a poison center/doctor. If exposed or concerned: Get medical

advice/attention. Do NOT induce vomiting.

Storage Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

## 3. Composition/information on ingredients

#### **Mixtures**

Chemical name	Common name and synonyms	CAS number	%
Butane		106-97-8	20 - 40

Chemical name	Common name and synonyms	CAS number	%
Mineral Spirits		8052-41-3	20 - 40
Propane		74-98-6	10 - 20
Synthetic Isoparaffinic Hydrocarbon		64741-66-8	10 - 20
Other components below reportable leve	els		20 - 40

<sup>\*</sup>Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

#### 4. First-aid measures

InhalationIf symptoms develop move victim to fresh air. Get medical attention if symptoms persist.Skin contactWash off with soap and water. Get medical attention if irritation develops and persists.

Eye contact Rinse with water. Get medical attention if irritation develops and persists.

**Ingestion** Rinse mouth. Get medical attention if symptoms occur.

Most important symptoms/effects, acute and

symptoms/effects, acute and delayed

Dizziness. Aspiration may cause pulmonary edema and pneumonitis. Prolonged exposure may cause chronic effects.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

General information

IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

## 5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Powder. Foam. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Contents under pressure. Pressurized container may explode when exposed to heat or flame.

Special protective equipment and precautions for firefighters

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Fire-fighting equipment/instructions

Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not

breathe fumes.

**General fire hazards** Extremely flammable aerosol.

#### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Do not breathe gas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Prevent entry into waterways, sewer, basements or confined areas. For waste disposal, see section 13 of the SDS.

**Environmental precautions** 

Avoid discharge into drains, water courses or onto the ground.

#### 7. Handling and storage

#### Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Do not breathe gas. When using, do not eat, drink or smoke. Use only in well-ventilated areas. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

### Conditions for safe storage, including any incompatibilities

Level 3 Aerosol.

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Refrigeration recommended. Store away from incompatible materials (see Section 10 of the SDS).

V-1--

## 8. Exposure controls/personal protection

### Occupational exposure limits

Components	Туре	Value	
Mineral Spirits (CAS 8052-41-3)	PEL	2900 mg/m3	
,		500 ppm	
Propane (CAS 74-98-6)	PEL	1800 mg/m3	
		1000 ppm	
<b>US. ACGIH Threshold Limit Valu</b>	es		
Components	Туре	Value	
Butane (CAS 106-97-8)	STEL	1000 ppm	
Mineral Spirits (CAS 8052-41-3)	TWA	100 ppm	
US. NIOSH: Pocket Guide to Che	mical Hazards		
Components	Туре	Value	
Butane (CAS 106-97-8)	TWA	1900 mg/m3	
,		800 ppm	
Mineral Spirits (CAS 8052-41-3)	Ceiling	1800 mg/m3	
-,	TWA	350 mg/m3	
Propane (CAS 74-98-6)	TWA	1800 mg/m3	
. ,		1000 ppm	

# **Biological limit values**

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

## Individual protection measures, such as personal protective equipment

Eye/face protection If contact is likely, safety glasses with side shields are recommended.

Hand protection

Wear appropriate chemical resistant gloves.

Skin protection

Other Use of an impervious apron is recommended.

Skin protection

Respiratory protection If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an

air-supplied respirator.

Wear appropriate thermal protective clothing, when necessary. Thermal hazards

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

Product name: 14 OZ ENVIRO-SEAL PARTS PROTECTOR

Product #: 74173 Version #: 09 Issue date: 04-22-2015

## 9. Physical and chemical properties

**Appearance** 

Physical state Gas.
Form Aerosol.
Color Dark brown.

Odor solvent
Odor threshold Not available.
PH Not available.
Melting point/freezing point Not available.

Initial boiling point and boiling

range

302 °F (150 °C) estimated

Flash point -156.0 °F (-104.4 °C) Propellant estimated

Evaporation rate Not available.

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower

0.9 % estimated

(%)

Flammability limit - upper

(%)

Not available.

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure 43.57 psig @70F estimated

Vapor density Not available.

Relative density Not available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature 743 °F (395 °C) estimated

**Decomposition temperature** Not available. **Viscosity** Not available.

Other information

Specific gravity 0.426 estimated

### 10. Stability and reactivity

**Reactivity**The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous Hazardous polymerization does not occur.

reactions

**Conditions to avoid**Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materialsStrong oxidizing agents. Nitrates. Fluorine. Chlorine.Hazardous decompositionNo hazardous decomposition products are known.

products

## 11. Toxicological information

## Information on likely routes of exposure

**Ingestion** Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious

chemical pneumonia.

**Inhalation** May cause damage to organs through prolonged or repeated exposure by inhalation.

Skin contact

No adverse effects due to skin contact are expected.

Eye contact

Direct contact with eyes may cause temporary irritation.

Symptoms related to the physical, chemical and toxicological characteristics

Dizziness. Aspiration may cause pulmonary edema and pneumonitis.

Information on toxicological effects

Acute toxicity May be fatal if swallowed and enters airways.

Rat

Components Species Test Results

Butane (CAS 106-97-8)

Acute

Inhalation

LC50 Mouse

1237 mg/l, 120 Minutes

52 %, 120 Minutes

Propane (CAS 74-98-6)

Acute

Inhalation

LC50 Mouse 1237 mg/l, 120 Minutes

52 %, 120 Minutes

Rat 1355 mg/l

658 mg/l/4h

1355 mg/l

Synthetic Isoparaffinic Hydrocarbon (CAS 64741-66-8)

Acute

Dermal

LD50 Rabbit > 1900 mg/kg, 24 Hours

Inhalation

LC50 Rat > 5020 mg/m3, 4 Hours

> 4980 mg/m3

> 4980 mg/m3, 4 Hours

> 4.96 mg/l, 4 Hours

Oral

LD50 Rat 4820 mg/kg

**Skin corrosion/irritation** Not available.

Serious eye damage/eye

irritation

Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

Respiratory sensitization Not available.

**Skin sensitization** This product is not expected to cause skin sensitization.

**Germ cell mutagenicity** May cause genetic defects.

Carcinogenicity May cause cancer.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

**Reproductive toxicity**This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Respiratory system. Skin. Kidneys. Central nervous system. Eyes. Causes damage to organs

through prolonged or repeated exposure.

**Aspiration hazard** May be fatal if swallowed and enters airways.

**Chronic effects** Causes damage to organs through prolonged or repeated exposure.

Product name: 14 OZ ENVIRO-SEAL PARTS PROTECTOR
Product #: 74173 Version #: 09 Issue date: 04-22-2015

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

## 12. Ecological information

**Ecotoxicity** 

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

**Test Results** Components Species

Synthetic Isoparaffinic Hydrocarbon (CAS 64741-66-8)

Aquatic

IC50 Algae 30000 mg/L, 72 Hours Algae

\* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available. Partition coefficient n-octanol / water (log Kow)

Butane 2.89 Mineral Spirits 3.16 - 7.15Propane 2.36

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

#### 13. Disposal considerations

**Disposal instructions** Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents

under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance

with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

The waste code should be assigned in discussion between the user, the producer and the waste Hazardous waste code

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Do not re-use empty containers.

## 14. Transport information

DOT

UN1950 **UN number** 

**UN** proper shipping name Aerosols, flammable

Transport hazard class(es)

Class 2.1 Subsidiary risk 2.1 Label(s)

**Packing group** Not applicable.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Special provisions N82 Packaging exceptions 306 None Packaging non bulk Packaging bulk None

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

**IATA** 

**UN** number UN1950

**UN** proper shipping name Aerosols, flammable

Transport hazard class(es)

**Class** 2.1 Subsidiary risk 2.1 Label(s)

Packing group Not applicable. **Environmental hazards** No.

Other information

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Passenger and cargo

aircraft

Forbidden.

Forbidden. Cargo aircraft only **Packaging Exceptions** LTD QTY

**IMDG** 

UN1950 **UN** number **UN** proper shipping name **AEROSOLS** 

Transport hazard class(es)

Class 2.1 Subsidiary risk 2.1 Label(s)

Not applicable. **Packing group** 

**Environmental hazards** 

Marine pollutant No.

**EmS** Not available.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

LTD QTY **Packaging Exceptions** Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78 and

the IBC Code

DOT



IATA; IMDG



## 15. Regulatory information

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication US federal regulations

Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

**CERCLA Hazardous Substance List (40 CFR 302.4)** 

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

## Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - Yes Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No

### SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous No

chemical

SARA 313 (TRI reporting)

Not regulated.

### Other federal regulations

#### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

#### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Butane (CAS 106-97-8) Propane (CAS 74-98-6)

**Safe Drinking Water Act** 

Not regulated.

(SDWA)

#### **US** state regulations

#### **US. Massachusetts RTK - Substance List**

Butane (CAS 106-97-8)

Mineral Spirits (CAS 8052-41-3)

Propane (CAS 74-98-6)

#### US. New Jersey Worker and Community Right-to-Know Act

Butane (CAS 106-97-8)

Mineral Spirits (CAS 8052-41-3)

Propane (CAS 74-98-6)

#### US. Pennsylvania Worker and Community Right-to-Know Law

Butane (CAS 106-97-8)

Mineral Spirits (CAS 8052-41-3)

Propane (CAS 74-98-6)

#### **US. Rhode Island RTK**

Butane (CAS 106-97-8)

Propane (CAS 74-98-6)

#### **US. California Proposition 65**

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

#### International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

<sup>\*</sup>A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)
A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

## 16. Other information, including date of preparation or last revision

**Issue date** 04-22-2015

Version # 09

**Disclaimer** The information provided in this Safety Data Sheet is correct to the best of our knowledge,

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.

Product name: 14 OZ ENVIRO-SEAL PARTS PROTECTOR Product #: 74173 Version #: 09 Issue date: 04-22-2015