Safety Data Sheet

Revised On 03/19/2015

I Identification of the substance an	id manufacturer
Trade name:	
Product code:	
IBS Part Number Product category	82057 PC9a Paints and coatings.
Manufacturer/Supplier:	Seymour of Sycamore
	917 Crosby Avenue, Sycamore, IL 60178
-	Phone: 815-895-9101 www.seymourpaint.com
Emergency telephone number:	CHEMTEL 1-800-255-3924, or 813-248-0585.
Hazard(s) identification	
Classification of the substance or mi	
Flam. Aerosol 1 H222 Extremely flam	
	nder pressure; may explode if heated.
Carc. 2 H351 Suspected of ca	
	nage to organs through prolonged or repeated exposure.
Eye Irrit. 2A H319 Causes serious GHS Hazard pictograms	\sim \sim \sim \sim
ono nazara piologranis	$\langle \mathfrak{m} \rangle \langle \mathfrak{m} \rangle \langle \mathfrak{m} \rangle \langle \mathfrak{m} \rangle$
	$\forall \lor \lor \forall \forall$
	GHS02 GHS04 GHS07 GHS08
Signal word	Danger
Hazard statements	Extremely flammable aerosol.
	Contains gas under pressure; may explode if heated.
	Causes serious eye irritation. Suspected of causing cancer.
	May cause damage to organs through prolonged or repeated exposure.
Precautionary statements	If medical advice is needed, have product container or label at hand.
	Keep out of reach of children. Read label before use.
	Obtain special instructions before use.
	Keep away from heat/sparks/open flames/hot surfaces No smoking.
	Do not spray on an open flame or other ignition source.
	Pressurized container: Do not pierce or burn, even after use. Wash hands thoroughly after handling.
	Wear protective gloves/protective clothing/eye protection/face protection. Do not handle until all safety precautions have been read and understood.
	Do not handle until all safety precautions have been read and understood.
	Do not breathe dust/fume/gas/mist/vapors/spray. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if prese
	and easy to do. Continue rinsing.
	Get medical advice/attention if you feel unwell.
	IF exposed or concerned: Get medical advice/attention. If eye irritation persists: Get medical advice/attention.
	Store locked up.
	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
	Store in a well-ventilated place. Dispose of contents/container in accordance with local/regional/national/internation
	regulations.
Composition/information on ingre	adionts
Chemical characterization: Mixtures	
Chemical Description:	This product is a mixture of the substances listed below with nonhazardous additions.
Dangerous components:	
64742-89-8 VM&P Naphtha	18.14
74-98-6 propane 1317-65-3 Calcium Carbonate	15.13 11.75
106-97-8 n-butane	8.889
64742-47-8 Mineral Spirits	3.859
110-19-0 isobutyl acetate	3.2%
First-aid measures	
After inhalation:	Supply fresh air; consult doctor in case of complaints.
After skin contact:	Remove contaminated clothing. Wash exposed area with soap and water. Rinse opened eye for several minutes under running water. Then consult a doctor.
After eye contact:	Rinse opened eye for several minutes under running water. Then consult a doctor.
After swallowing:	Rinse mouth with water. Do not induce vomiting.
Most important symptoms and effects:	Dizziness
Indication of any immediate medical	
attention needed:	No further relevant information available.
Fire-fighting measures Extinguishing agents:	CO2, extinguishing powder or water spray. Fight larger fires with water spray.
	LUZ extinduishind howder or water shray. Fight larger tires with water shray

Special hazards:

Can form explosive gas-air mixtures.

(Contd. on page 2)

Safety Data Sheet		
Printing date 04/16/2015	Revised On 03/19/2015	
Trade name: STRIPE FLUORESCENT ORANGE		
Protective equipment for	(Contd. of page 1)	
firefighters:	A respiratory protective device may be necessary.	
-		
6 Accidental release measures		
Personal precautions, protective		
equipment and emergency procedures:	Use respiratory protective device against the effects of fumes/dust/aerosol.	
Methods and material for		
containment and cleaning up:	Absorb liquid components with liquid-binding material.	
7 Handling and storage	Lies only in well wantilated areas	
Precautions for safe handling Storage requirements:	Use only in well ventilated areas. Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing	
	conditions. Store locked up.	
8 Exposure controls/personal protection		
Components with limit values that require monitoring at the workplace:		
74-98-6 propane	/m3_1000 ppm	
PEL (USA) Long-term value: 1800 mg REL (USA) Long-term value: 1800 mg		
TLV (USA) refer to Appendix F	,	
106-97-8 n-butane		
REL (USA) Long-term value: 1900 mg	/m³, 800 ppm	
TLV (USA) Short-term value: 2370 mg	/m³, 1000 ppm	
110-19-0 isobutyl acetate PEL (USA) Long-term value: 700 mg/r	n³ 150 ppm	
REL (USA) Long-term value: 700 mg/r	n ³ , 150 ppm	
TLV (USA) Long-term value: 713 mg/r		
Hygienic protection:	Wash hands after use. Do not eat or drink while working.	
Breathing equipment:	A respirator is generally not necessary when using this product outdoors or in large open areas.	
-	In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical	
	hygeine.	
Hand protection:	Protective gloves. The glove material must be impermeable and resistant to the substance.	
Eye protection:	Tightly sealed goggles	
9 Physical and chemical properties		
Appearance:	Aerosol.	
Odor:	Aromatic	
Odor threshold:	Not determined.	
pH-value: Melting point/Melting range	Not determined. Undetermined.	
Boiling point:	-44 °C (-47 °F)	
Flash point:	-19 °C (-2 °F)	
Flammability (solid, gas):	Extremely flammable.	
Decomposition temperature:	Not determined.	
Auto igniting:	Product is not self-igniting.	
Danger of explosion:	In use, may form flammable/explosive vapour-air mixture.	
Lower Explosion Limit: Upper Explosion Limit:	1.7 Vol % 10.9 Vol %	
Vapor pressure:	Not determined.	
Relative Density:	Between 0.77 and 0.85 (Water equals 1.00)	
Vapour density Evaporation rate	Not determined. Not applicable.	
Partition coefficient: n-octonal/water		
Solubility:	Not determined.	
Viscosity:	Not determined.	
VOC content:	525.6 g/l / 4.39 lb/gl	
VOC content (less exempt solvents): Water:	50.5 % 24.4 %	
MIR Value:	0.57	
Solids content:	24.2 %	
10 Stability and reactivity		
Reactivity: Conditions to avoid:	Stable at normal temperatures. Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing	
	temperatures.	
Chemical stability: Possibility of hazardous reactions:	Not fully evaluated.	
FOSSISHILY OF HAZALUOUS TEACTIONS:	No dangerous reactions known. (Contd. on page 3)	

Page 2/4

Page 3/4

Printing date 04/16/2015	Safety Data Sneet Revised On 03/19/2015		
Trade name: STRIPE FLUORESCENT ORANGE			
	(Contd. of page 2)		
Incompatible materials: Hazardous decomposition:	No further relevant information available. No dangerous decomposition products known.		
11 Toxicological information			
LD/LC50 values that are relevant fo	r classification:		
106-97-8 n-butane			
Inhalative LC50/4 h 658 mg/l (rat)			
110-19-0 isobutyl acetate Oral LD50 4763 mg/kg (rbt)			
Information on toxicological effects			
Skin effects:	No irritant effect.		
Eye effects: Sensitization:	No irritating effect. No sensitizing effects known.		
Carcinogenic categories			
IARC (International Agency for Research on Cancer)			
None of the ingredients is listed.	,		
NTP (National Toxicology Program)			
None of the ingredients is listed.			
12 Ecological information			
Aquatic toxicity: Persistence and degradability:	Hazardous for water, do not empty into drains. The product is degradable after prolonged exposure to natural weathering processes.		
Bioaccumulative potential:	No further relevant information available.		
Mobility in soil: Other adverse effects:	No further relevant information available. No further relevant information available.		
13 Disposal considerations			
	state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must eat or cut empty containers with electric or gas torches.		
be disposed of responsibly. Do not he Recommendation :	eat or cut empty containers with electric or gas torches. Completely empty cans should be recycled.		
Recommendation.			
14 Transport information			
UN-Number	UN1950		
DOT DOT	N/A Consumer Commodity ORM-D		
-	Aerosols, flammable		
ADR Transport hazard class(es):	1950 Aerosols		
Class	2.1		
Marine pollutant: Special precautions for user:	No Warning: Gases		
EMS Number:	F-D,S-Ŭ		
Quantity limitations	On passenger aircraft/rail: 75 kg On cargo aircraft only: 150 kg		
ADR			
Excepted quantities (EQ)	Code: E0		
	Not permitted as Excepted Quantity		
IMDG			
Limited quantities (LQ) Excepted quantities (EQ)	1L Code: E0		
	Not permitted as Excepted Quantity		
Packaging Group: UN "Model Regulation":	UN1950, Aerosols, 2.1		
15 Regulatory information			
SARA Section 355 (extremely hazar	dous substances):		
None of the ingredients in this produc			
SARA Section 313 (Specific toxic c			
None of the ingredients is listed.			
CPSC:	This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.		
	California Proposition 65 chemicals known to cause cancer: 100-41-4 ethyl benzene		
CANADIAN ENVIRONMENTAL			
PROTECTION ACT:	All hazardous ingredients for this product appear on the Canadian Domestice Substance List.		
EPA:			
110-19-0 isobutyl acetate	D		
16 Other information			
16 Other information Contact:	Regulatory Affairs		
Comaci.	(Contd. on page 4)		

Date of preparation / last revision 04/16/2015 / - (Contd. of page 3)

Page 4/4

Revised On 03/19/2015