Safety Data Sheet



Revision Number: 002.0

1. PRODUCT AND COMPANY IDENTIFICATION

Product name:

 Product type:
 Epoxy

 Restriction of Use:
 None

 Company address:
 Henkel Corporation

 One Henkel Way
 Rocky Hill, Connecticut 06067

LOCTITE PC 3965 known as Fast Set Steel Epoxy Epoxy Hardener None identified IDH number:

702219

Item number:96604 - HardenerRegion:United StatesContact information:Telephone:(860) 571-5100MEDICAL EMERGENCY Phone:Poison Control Center1-877-671-4608 (toll free) or 1-303-592-1711TRANSPORT EMERGENCY Phone:CHEMTREC1-800-424-9300 (toll free) or 1-703-527-3887Internet:www.henkelna.com

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW WARNING: CAUSES SKIN IRRITATION. MAY CAUSE AN ALLERGIC SKIN REACTION. CAUSES SERIOUS EYE IRRITATION.

| HAZARD CLASS | HAZARD CATEGORY |
|--------------------|-----------------|
| SKIN IRRITATION | 2 |
| EYE IRRITATION | 2A |
| SKIN SENSITIZATION | 1 |



Precautionary Statements

| Prevention: | Avoid breathing dust or fumes. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wear eye and face protection. Wear protective gloves. |
|-------------|--|
| Response: | IF ON SKIN: Wash with plenty of soap and water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to remove. Continue rinsing. If skin irritation or rash occurs: Get medical attention. If eye irritation persists: Get medical attention. Take off contaminated clothing. |
| Storage: | Not prescribed |
| Disposal: | Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations. |

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

| Hazardous Component(s) | CAS Number | Percentage* | |
|-------------------------|-------------|-------------|--|
| Polymercaptan hardener | Proprietary | 60 - 100 | |
| Substituted aminophenol | Proprietary | 5 - 10 | |
| Aluminum | 7429-90-5 | 1 - 5 | |
| Titanium dioxide | 13463-67-7 | 1 - 5 | |
| Substituted aminophenol | Proprietary | 1 - 5 | |

* Exact percentage is a trade secret. Concentration range is provided to assist users in providing appropriate protections.

| 4. FIRST AID MEASURES | | | |
|------------------------------------|---|--|--|
| Inhalation: | Move to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention. | | |
| Skin contact: | Immediately flush skin with plenty of water (using soap, if available). Remove contaminated clothing and footwear. Wash clothing before reuse. Thoroughl clean shoes before reuse. Get medical attention. | | |
| Eye contact: | Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention. | | |
| Ingestion: | DO NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention. | | |
| Symptoms: | See Section 11. | | |
| 5. | FIRE FIGHTING MEASURES | | |
| Extinguishing media: | Water spray (fog), foam, dry chemical or carbon dioxide. | | |
| Special firefighting procedures: | Wear self-contained breathing apparatus and full protective clothing, such a turn-out gear. | | |
| Unusual fire or explosion hazards: | In case of fire, keep containers cool with water spray. Closed containers marked rupture (due to build up of pressure) when exposed to extreme heat. | | |
| Hazardous combustion products: | Oxides of carbon. Irritating organic fragments. | | |

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

| Environmental precautions: | Do not allow product to enter sewer or waterways. | |
|----------------------------|--|--|
| Clean-up methods: | Remove all sources of ignition. Immediately contact emergency personnel. Evacuate and ventilate spill area; dike spill to prevent entry into water system; wear full protective equipment during clean-up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Scrape up as much material as possible. Clean residue with soap and water. Store in a closed container until ready for disposal. Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up. | |

7. HANDLING AND STORAGE

Handling:

Do not taste or swallow. Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Keep container closed. Refer to Section 8.

Storage:

Store in original container until ready to use. Keep container tightly closed and in a cool, well-ventilated place away from incompatible materials. Store away from heat, sparks, flames, or other sources of ignition.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

| Hazardous Component(s) | ACGIH TLV | OSHA PEL | AIHA WEEL | OTHER |
|-------------------------|-------------------------------------|--|-----------|-------|
| Polymercaptan hardener | None | None | None | None |
| Substituted aminophenol | None | None | None | None |
| Aluminum | 1 mg/m3 TWA Respirable fraction. | 5 mg/m3 PEL (as Al) Respirable dust. 15 mg/m3 PEL (as Al) Total dust. | None | None |
| Titanium dioxide | 10 mg/m3 TWA | 15 mg/m3 PEL Total dust. | None | None |
| Substituted aminophenol | None | None | None | None |

Respiratory protection:

Engineering controls:

Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits.

Use NIOSH approved respirator if there is potential to exceed exposure limit(s).

showers and eye wash stations should be available.

Eye/face protection:

Skin protection:

Use chemical resistant, impermeable clothing including gloves and either an apron or body suit to prevent skin contact.

Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists. Safety

9. PHYSICAL AND CHEMICAL PROPERTIES

| Physical state: | Paste |
|--|---|
| Color: | Gray, White |
| Odor: | Mercaptan |
| Odor threshold: | Not available. |
| pH: | Not available. |
| Vapor pressure: | Not available. |
| Boiling point/range: | Not determined |
| Melting point/ range: | Not available. |
| Specific gravity: | 1.663 |
| Vapor density: | >1 |
| Flash point: | > 93.4 °C (> 200.12 °F) Pensky Martens closed cup |
| Flammable/Explosive limits - lower: | Not available. |
| Flammable/Explosive limits - upper: | Not available. |
| Autoignition temperature: | Not available. |
| Evaporation rate: | Slower than butyl acetate. |
| Solubility in water: | Insoluble |
| Partition coefficient (n-octanol/water): | Not available. |
| VOC content: | < 1.0 %; < 10 g/l (value for resin and hardener together) (estimated) |
| Viscosity: | Not available. |
| Decomposition temperature: | Not available. |

10. STABILITY AND REACTIVITY

| Stability: | Stable under normal conditions of storage and use. |
|--------------------------------------|---|
| Hazardous reactions: | None under normal processing. |
| Hazardous decomposition products: | Oxides of carbon. Irritating organic fragments. |
| Incompatible materials: | Strong acids and strong bases. Strong oxidizing agents. |
| Reactivity: | Not available. |
| Conditions to avoid: | Excessive heat. Store away from incompatible materials. Heat, flames, sparks and other sources of ignition. |
| | |

11. TOXICOLOGICAL INFORMATION

| Relevant routes of exposure: | Skin, Inhalation, Eyes, Ingestion |
|------------------------------|-----------------------------------|
| | |

Potential Health Effects/Symptoms

| Inhalation: | Inhalation of vapors or mists of the product may be irritating to the respiratory system. |
|---------------|---|
| Skin contact: | Causes skin irritation. May cause allergic skin reaction. |
| Eye contact: | Causes serious eye irritation. |
| Ingestion: | May cause gastrointestinal tract irritation if swallowed. |

| Hazardous Component(s) | LD50s and LC50s | Immediate and Delayed Health Effects |
|-------------------------|-----------------|--|
| Polymercaptan hardener | None | No Records |
| Substituted aminophenol | None | Irritant, Allergen |
| Aluminum | None | Central nervous system, Irritant, Lung |
| Titanium dioxide | None | Irritant, Respiratory, Some evidence of carcinogenicity |
| Substituted aminophenol | None | No Records |

| Hazardous Component(s) | NTP Carcinogen | IARC Carcinogen | OSHA Carcinogen (Specifically Regulated) |
|-------------------------|----------------|-----------------|---|
| Polymercaptan hardener | No | No | No |
| Substituted aminophenol | No | No | No |
| Aluminum | No | No | No |
| Titanium dioxide | No | Group 2B | No |
| Substituted aminophenol | No | No | No |

12. ECOLOGICAL INFORMATION

Ecological information:

Not available.

13. DISPOSAL CONSIDERATIONS Information provided is for unused product only. Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal. Hazardous waste number: Not a RCRA hazardous waste. **14. TRANSPORT INFORMATION** The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration. U.S. Department of Transportation Ground (49 CFR) Proper shipping name: Not regulated Hazard class or division: None Identification number: None Packing group: None International Air Transportation (ICAO/IATA) Proper shipping name: Not regulated Hazard class or division: None Identification number: None Packing group: None Water Transportation (IMO/IMDG) Proper shipping name: Not regulated Hazard class or division: None Identification number: None Packing group: None **15. REGULATORY INFORMATION United States Regulatory Information** TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory. TSCA 12 (b) Export Notification: None above reporting de minimis CERCLA/SARA Section 302 EHS: None above reporting de minimis CERCLA/SARA Section 311/312: Immediate Health, Delayed Health **CERCLA/SARA Section 313:** This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). Aluminum (CAS# 7429-90-5). **California Proposition 65:** This product contains a chemical known in the State of California to cause cancer.

Canada Regulatory Information

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic Substances List.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: New Safety Data Sheet format.

Prepared by: Sheila Gines, Regulatory Affairs Specialist

Issue date: 08/14/2014

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.