

Revision Number: 003.1 Issue date: 10/13/2014

## 1. PRODUCT AND COMPANY IDENTIFICATION

LOCTITE EA 9017 B known as Product name:

**LOCTITE FM POXY PAK 1FO PT B** 

Product type: **Epoxy Hardener** Restriction of Use: None identified

Company address: Henkel Corporation One Henkel Way

Rocky Hill, Connecticut 06067

DANGER:

IDH number: 1324014

Item number: 81120 - Hardener Region: **United States** 

**Contact information:** Telephone: (860) 571-5100

MEDICAL EMERGENCY Phone: Poison Control Center

1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

## 2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW	
CAUSES SEVERE SKIN BURNS AND EYE DAMAGE.	
MAY CAUSE AN ALLERGIC SKIN REACTION.	

HAZARD CLASS	HAZARD CATEGORY
SKIN CORROSION	1B
SERIOUS EYE DAMAGE	1
SKIN SENSITIZATION	1





#### **Precautionary Statements**

Prevention: Do not breathe vapors, mist, or spray. Wash thoroughly after handling. Contaminated work

clothing should not be allowed out of the workplace. Wear protective gloves, eye protection,

and face protection.

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off Response:

immediately all contaminated clothing. IF INHALED: Remove person to fresh air and keep

comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to remove. Continue rinsing. Immediately call a poison control center or physician. If skin irritation or rash occurs: Get medical attention. Wash contaminated clothing

before reuse.

Storage: Store locked up.

Disposal: Dispose of contents and/or container according to Federal, State/Provincial and local

governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

## 3. COMPOSITION / INFORMATION ON INGREDIENTS

IDH number: 1324014 Product name: LOCTITE EA 9017 B known as LOCTITE FM POXY PAK 1FO PT B Page 1 of 6

Hazardous Component(s)	CAS Number	Percentage*	
Polymercaptan hardener	Proprietary	60 - 100	
m-Phenylenebis(methylamine)	1477-55-0	10 - 30	
Substituted aminophenol	Proprietary	5 - 10	
Phenol	108-95-2	1 - 5	
Reactive Silane	Proprietary	0.1 - 1	
Substituted aminophenol	Proprietary	0.1 - 1	

<sup>\*</sup> Exact percentage is a trade secret. Concentration range is provided to assist users in providing appropriate protections.

## 4. FIRST AID MEASURES

Inhalation: Move to fresh air. If not breathing, give artificial respiration. Get medical

attention.

Skin contact: Immediately flush skin with plenty of water (using soap, if available). Remove

contaminated clothing and footwear. Get medical attention.

Eye contact: Rinse immediately with plenty of water, also under the eyelids, for at least 15

minutes. Get medical attention.

Ingestion: DO NOT induce vomiting unless directed to do so by medical personnel. Get

medical attention.

Symptoms: See Section 11.

IDH number: 1324014

Notes to physician: Treat symptomatically and supportively.

## 5. FIRE FIGHTING MEASURES

Extinguishing media: Water spray (fog), foam, dry chemical or carbon dioxide.

Special firefighting procedures: Wear self-contained breathing apparatus and full protective clothing, such as

turn-out gear.

Unusual fire or explosion hazards: In case of fire, keep containers cool with water spray. Closed containers may

rupture (due to build up of pressure) when exposed to extreme heat.

**Hazardous combustion products:** Oxides of carbon. Oxides of nitrogen. Irritating organic fragments.

# 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

**Environmental precautions:** Do not allow product to enter sewer or waterways. Remove all sources of

ignition. Ventilate area. Wear appropriate protective equipment and clothing during clean-up. Prevent further leakage or spillage if safe to do so.

Clean-up methods: Absorb spill with inert material. Shovel material into appropriate container for

disposal. Dispose of according to Federal, State and local governmental

regulations.

## 7. HANDLING AND STORAGE

**Handling:** Use only with adequate ventilation. Prevent contact with eyes, skin and

clothing. Do not breathe vapor and mist. Wash thoroughly after handling.

Keep container closed. Refer to Section 8.

Storage: Keep container tightly closed and in a cool, well-ventilated place away from

incompatible materials. Store away from heat, sparks, flames, or other

sources of ignition.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Polymercaptan hardener	None	None	None	None
m-Phenylenebis(methylamine)	0.1 mg/m3 Ceiling (SKIN)	None	None	None
Substituted aminophenol	None	None	None	None
Phenol	5 ppm TWA (SKIN)	5 ppm (19 mg/m3) PEL (SKIN)	None	None
Reactive Silane	None	None	None	None
Substituted aminophenol	None	None	None	None

Engineering controls: Provide adequate local exhaust ventilation to maintain worker exposure below

exposure limits.

Respiratory protection: Use a NIOSH approved air-purifying respirator if the potential to exceed

established exposure limits exists.

Eye/face protection: Safety googles or safety glasses with side shields. Full face protection should

be used if the potential for splashing or spraying of product exists. Safety

showers and eye wash stations should be available.

Skin protection: Use chemical resistant, impermeable clothing including gloves and either an

apron or body suit to prevent skin contact.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Liquid

Amber, Translucent Color: Odor: Amine, Mercaptan Odor threshold: Not available. :Ha Not available. Vapor pressure: Not available. Boiling point/range: Not available. Melting point/ range: Not available. Specific gravity: 1.04

Vapor density: Not available.

Flash point: > 93 °C (> 199.4 °F) Tagliabue closed cup

Flammable/Explosive limits - lower:

Flammable/Explosive limits - upper:

Autoignition temperature:

Evaporation rate:

Solubility in water:

Partition coefficient (n-octanol/water):

Not available.

Insoluble

Not available.

**VOC content:** 3.77 %; 0.38 g/l EPA Method 24

Viscosity: Not available.

Decomposition temperature: Not available.

IDH number: 1324014 Product name: LOCTITE EA 9017 B known as LOCTITE FM POXY PAK 1FO PT B
Page 3 of 6

# 10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions of storage and use.

Hazardous reactions: None under normal processing.

Hazardous decomposition

products:

IDH number: 1324014

Oxides of carbon. Oxides of nitrogen. Irritating organic fragments.

**Incompatible materials:** Strong acids and strong bases. Strong oxidizing agents.

Reactivity: Not available.

Conditions to avoid: Elevated temperatures. Heat, flames, sparks and other sources of ignition. Store away from

incompatible materials.

## 11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes, Ingestion

#### Potential Health Effects/Symptoms

Inhalation: Toxic by inhalation. Respiratory tract burns. May cause irritation to nose and throat.

**Skin contact:** Corrosive to skin. Causes skin burns. May cause allergic skin reaction.

**Eye contact:** Causes serious eye damage. Burns.

Ingestion: Irritation and corrosive action can occur in the mouth, stomach tissue and digestive tract if

swallowed. May cause burns of mouth and throat if swallowed.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Polymercaptan hardener	None	No Records
m-Phenylenebis(methylamine)	None	Irritant, Liver, Kidney, Corrosive
Substituted aminophenol	None	Irritant, Allergen
Phenol	Oral LD50 (RAT) = 317 mg/kg Oral LD50 (RAT) = 530 mg/kg Dermal LD50 (RAT) = 669 mg/kg Dermal LD50 (RABBIT) = 850 mg/kg	Blood, Cardiac, Corrosive, Developmental, Eyes, Irritant, Kidney, Liver, Mutagen, Nervous System, Skin, Vascular
Reactive Silane	None	Irritant, Allergen
Substituted aminophenol	None	No Records

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Polymercaptan hardener	No	No	No
m-Phenylenebis(methylamine)	No	No	No
Substituted aminophenol	No	No	No
Phenol	No	No	No
Reactive Silane	No	No	No
Substituted aminophenol	No	No	No

# 12. ECOLOGICAL INFORMATION

Ecological information: Not available.

Page 4 of 6

## 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

**Hazardous waste number:** It is the responsibility of the user to determine if an item is hazardous as

defined in the Resource Conservation and Recovery Act (RCRA) at the time of disposal. Product uses, transformations, mixtures, processes, etc., may render the resulting material hazardous, under the criteria of ignitability, corrosivity, reactivity and toxicity characteristics of the Toxicity Characteristics

Leaching Procedure (TCLP) 40 CFR 261.20-24.

#### 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Amines, liquid, corrosive, n.o.s. (m-Xylylenediamine)

Hazard class or division: 8
Identification number: UN 2735
Packing group: II
DOT Hazardous Substance(s): Phenol

International Air Transportation (ICAO/IATA)

**Proper shipping name:** Amines, liquid, corrosive, n.o.s. (m-Xylylenediamine)

Hazard class or division: 8
Identification number: UN 2735
Packing group: II

Water Transportation (IMO/IMDG)

Proper shipping name: AMINES, LIQUID, CORROSIVE, N.O.S. (m-Xylylenediamine)

Hazard class or division: 8
Identification number: UN 2735
Packing group: II

## 15. REGULATORY INFORMATION

**United States Regulatory Information** 

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act

Inventory.

TSCA 12 (b) Export Notification: None above reporting de minimis

CERCLA/SARA Section 302 EHS: Phenol (CAS# 108-95-2).
CERCLA/SARA Section 311/312: Immediate Health, Delayed Health

CERCLA/SARA Section 313: This product contains the following toxic chemicals subject to the reporting requirements of

section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40

CFR 372). Phenol (CAS# 108-95-2).

CERCLA Reportable quantity: Phenol (CAS# 108-95-2) 1,000 lbs. (454 kg)

California Proposition 65: This product contains a chemical known to the State of California to cause birth defects or

other reproductive harm.

**Canada Regulatory Information** 

IDH number: 1324014

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic

Substances List.

#### 16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: New Safety Data Sheet format.

Product name: LOCTITE EA 9017 B known as LOCTITE FM POXY PAK 1FO PT B

Page 5 of 6

**Prepared by:** Sheila Gines, Regulatory Affairs Specialist

**Issue date:** 10/13/2014

IDH number: 1324014

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.