F

Page 1/5

| 1 Identification of the substance   | and manufacturer  |  |  |
|---|---|--|--|
| Trade name:   | NEW FARM & IMPLEMENT GREEN  |  |  |
| Product code:<br>IBS Part Number<br>Product category<br>Manufacturer/Supplier:              | 0000160268<br>81268<br>PC9a Paints and coatings.<br>Seymour of Sycamore<br>917 Crosby Avenue, Sycamore, IL 60178<br>Phone: 815-895-9101 www.seymourpaint.com  |  |  |
| Emergency telephone number:   | CHEMTEL 1-800-255-3924, or 813-248-0585.  |  |  |
| 2 Hazard(s) identification  |   |  |  |
| Carc. 2 H351 Suspected of<br>STOT RE 2 H373 May cause of<br>Eye Irrit. 2A H319 Causes serie | ammable aerosol.<br>s under pressure; may explode if heated.<br>of causing cancer.<br>damage to organs through prolonged or repeated exposure.  |  |  |
| Signal word<br>Hazard statements  | Danger<br>Extremely flammable aerosol.<br>Contains gas under pressure; may explode if heated.<br>Causes serious eye irritation.<br>Suspected of causing cancer.   |  |  |
| Precautionary statements  | May cause drowsiness or dizziness.<br>May cause damage to organs through prolonged or repeated exposure.<br>If medical advice is needed, have product container or label at hand.<br>Keep out of reach of children.<br>Read label before use.<br>Obtain special instructions before use.<br>Keep away from heat/sparks/open flames/hot surfaces No smoking.<br>Do not spray on an open flame or other ignition source.<br>Pressurized container: Do not pierce or burn, even after use.<br>Wash hands thoroughly after handling.<br>Use only outdoors or in a well-ventilated area.<br>Wear protective gloves/protective clothing/eye protection/face protection.<br>Do not breathe dust/fume/gas/mist/vapors/spray.<br>IF INHALED: Remove person to fresh air and keep comfortable for breathing.<br>If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present<br>and easy to do. Continue rinsing.<br>Call a poison center/doctor if you feel unwell.<br>If eye irritation persists: Get medical advice/attention.<br>Store locked up.<br>Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.<br>Store in a well-ventilated place. Keep container tightly closed.<br>Dispose of contents/container in accordance with local/regional/national/international<br>regulations. |  |  |
| 3 Composition/information on ingredients  |   |  |  |

|                          | on/information on ingro                   | edients   |        |
|--------------------------|---|---|--------|
| Chemical c<br>Chemical D | haracterization: Mixtures<br>Description: | This product is a mixture of the substances listed below with nonhazardous additions. |        |
|                          | components:                               |   |        |
| 67-64-1                  | Acetone                                   |   | 18.44% |
| 74-98-6 p                |   |   | 15.68% |
| 106-97-8 r               | n-butane                                  |   | 9.21%  |
| 7727-43-7 k              | barium sulfate, natural                   |   | 8.81%  |
| 2807-30-9                | Glycol Ether EP                           |   | 7.05%  |
|                          | methyl isobutyl ketone                    |   | 6.99%  |
| 107-87-9 N               | Methyl Propyl Ketone                      |   | 2.93%  |
| 1330-20-7 >              |   |   | 2.56%  |
| 108-65-6                 | PM acetate                                |   | 2.16%  |
| 110-19-0 i               | sobutyl acetate                           |   | 1.75%  |

| 4 First-aid measures                     |   |
|--|---|
| After inhalation:<br>After skin contact: | Supply fresh air; consult doctor in case of complaints.<br>Remove contaminated clothing. Wash exposed area with soap and water. |
| After eye contact:                       | Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.                                |
| After swallowing:                        | Rinse out mouth and then drink plenty of water.<br>Rinse mouth with water. Do not induce vomiting.                              |
| Most important symptoms and<br>effects:  | Dizziness   |
|  | (Contd. on page 2)  |

Safety Data Sheet

Page 2/5

| Trade name: NEW FARM & IMPLEMENT GREEN   (Contic or page 1)     Indication of any immediate medical attention needed.   No further relevant information available.     5 First-fighting messures Expectation needed.   C2. estinguishing proved or water spray. Fight larger fires with water spray. Can form explosive gas-at-in intrustres.     5 Accidental release messures   C2. estinguishing proved or water spray. Fight larger fires with water spray. Can form explosive gas-at-in intrustres.     6 Accidental release messures   Personal prezuitions, protective equipment. Keep unprotected persons away. User reported water adjustres of heat and direct sunlight. Do not warehouse in subfreezing or containment and cleaning up: Ensure adequate ventilated areas.     7 Handling and storage   Preculators for safe handling.     8 Exposure controls/personal protection   Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing ordinates. Store locked up.     7 Handling and storage   Preculators for safe handling.     8 Exposure controls/personal protection   Can form give 700 ppm     9 File (USA)   Long-term value: 2400 mg/m <sup>2</sup> , 1000 ppm     7 File (USA)   Long-term value: 1800 mg/m <sup>2</sup> , 1000 ppm     9 File (USA)   Long-term value: 1800 mg/m <sup>2</sup> , 1000 ppm     17 V (USA)   Short-term value: 1800 mg/m <sup>2</sup> , 1000 ppm     17 File (USA)   Long-term value: 1800 mg/m <sup>2</sup> , 1000 ppm     17 V (USA)<  | Printing date 04/15/201               | 5                        | Salety Data Sheet  | Revised On 02/02/2015 |  |
|---|---------------------------------------|--------------------------|--|-----------------------|--|
| Indication of any immediate medical<br>stansition needed:     No further relevant information available.       5 First-fighting measures<br>Extinguishing agents:<br>Special hazards:<br>Fractice experiment for<br>response protective experiment for such and energinor.<br>Conform explosive gas-air mixtures.     CO2, extinguishing powder or water spray. Fight larger fires with water spray.<br>Conform explosive gas-air mixtures.       6 Accidental release measures<br>Procedures:     Preparities with protective explored from explosive gas-air mixtures.       7 Handling and storage<br>Precautions for safe handling<br>Storage requirements.     Use only in well ventilated areas,<br>for safe handling<br>Storage requirements.       8 Exposure controlSpersonal protection<br>Components with limit value: 2400 mg/m <sup>1</sup> , 1000 ppm<br>Ret. (USA)<br>Long-term value: 2600 mg/m <sup>1</sup> , 1000 ppm<br>Ret. (USA)<br>Long-term value: 1600 mg/m <sup>2</sup> , 1000 ppm<br>Ret. (USA)<br>Long-term value: 270 mg/m <sup>2</sup> , 1000 ppm<br>Ret. (USA)<br>Long-term value: 1600 mg/m <sup>2</sup> , 1000 ppm<br>Ret. (USA)<br>Long-term value: 260 mg/m <sup>2</sup> , 1000 |                                       |                          |  |                       |  |
| Indication of any immediate medical<br>Number of the system   |                                       |                          |  |                       |  |
| attention needed:     No further relevant information available.       5 Fire-fighting measures<br>Extinguishing agents:     CO2, estinguishing powder or water spray. Fight larger fires with water spray.<br>Can form explosive gas all mixtures.       6 Accidental release measures<br>equipment and emergency<br>procedures:     Vear protective equipment. Keep unprotected persons away.<br>User respiratory protective device against the effects of furnes/dust/aerosol.       7 Handling and storage<br>Precautions for safe handling<br>Storage requirements:     Use only in well ventilated areas.<br>Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing<br>conditions. Store locked up.       8 Exposure controls/personal protection<br>Components with limit values that require monitoring at the workplace:<br>67-64-1 Acctore<br>PTEL (USA)     Long-term value. 240 mg/m², 1000 ppm<br>120 ppm<br>120 ppm<br>120 ppm<br>120 ppm<br>121 ppm<br>121 ppm<br>124 ppm<br>124 ppm<br>124 ppm<br>125 ppm<br>124 ppm<br>125 ppm<br>125 ppm<br>125 ppm<br>125 ppm<br>125 ppm<br>125 ppm<br>125 ppm<br>126 ppm<br>126 ppm<br>126 ppm<br>127 ppm<br>126 ppm<br>127 ppm<br>126 ppm<br>127 ppm<br>126 ppm<br>126 ppm<br>127 ppm<br>126 ppm<br>127 ppm<br>126 ppm<br>126 ppm<br>127 ppm<br>126 ppm<br>1                  | Indiantian of                         |                          |  | (Contd. of page 1)    |  |
| 5 Fire-fighting measures   CO2, extinguishing powder or water spray. Fight larger fires with water spray.     Special hazards:   CO2, extinguishing powder or water spray. Fight larger fires with water spray.     Special hazards:   Co1 of molecular spray.     Processions, protective equipment for firefighters.   A respiratory protective device may be necessary.     6 Accidental release measures   Personal processions, protective equipment. Keep unprotected persons away.     procedures:   Wear protective equipment. Keep unprotected persons away.     Water spray from source and spray fro   |                                       |                          |  |                       |  |
| Extinguishing agents:<br>Special Lazards:<br>Protective equipment for<br>inteligities:<br>A respiratory protective device may be necessary.<br>6 Accidential release measures<br>Period and material for<br>containment and eleaning up:<br>First equipment eleaning up:<br>First eleaning equipment eleaning up:<br>First eleaning equipment eleaning up:<br>First eleaning equipment eleaning up:<br>First eleaning equipment eleaning equipment eleaning equipment eleaning eleaning equipment eleaning e  |                                       |                          |  |                       |  |
| Extinguishing agents:<br>Special Lazards:<br>Protective equipment for<br>inteligities:<br>A respiratory protective device may be necessary.<br>6 Accidential release measures<br>Period and material for<br>containment and eleaning up:<br>First equipment eleaning up:<br>First eleaning equipment eleaning up:<br>First eleaning equipment eleaning up:<br>First eleaning equipment eleaning up:<br>First eleaning equipment eleaning equipment eleaning equipment eleaning eleaning equipment eleaning e  | 5 Fire-fighting                       | g measures               |  |                       |  |
| Protective equipment for<br>firefighters:     A respiratory protective device may be necessary.       6 Accidental release measures<br>Personal precautions, protective<br>equipment and denergency<br>procedures:     Waar protective device against the effects of lumes/dust/aerosol.       Wethods and material for<br>containment and cleaning up:     Ensure adequate ventilation.       7 Handling and storage<br>Precautions for safe handling<br>Storage requirements:     Use only in well ventilated areas.       8 Exposure controls/personal protection     Components with limit values that require monitoring at the workplace:       67 44-1 Actione.     Feed (USA)       PHEL (USA)     Long-term value: 2400 mg/m³, 1000 ppm<br>REL (USA)       Bill     Long-term value: 2400 mg/m³, 1000 ppm<br>REL (USA)       Bill     Long-term value: 1800 mg/m³, 1000 ppm<br>REL (USA)       PFEL (USA)     Long-term value: 1800 mg/m³, 1000 ppm<br>REL (USA)       Component with limit value: 1800 mg/m³, 1000 ppm<br>REL (USA)     Long-term value: 1800 mg/m³, 1000 ppm<br>REL (USA)       T46456 propane     FefE (VSA)     Long-term value: 1800 mg/m³, 1000 ppm<br>REL (USA)       TV (USA)     Short-term value: 1800 mg/m³, 1000 ppm<br>REL (USA)     Long-term value: 1800 mg/m³, 1000 ppm<br>REL (USA)       T46456 propane     FefE (VSA)     Long-term value: 1800 mg/m³, 1000 ppm<br>REL (USA)       TV (USA)     Short-term value: 1800 mg/m³, 10  | Extinguishin                          | g agents:                | CO2, extinguishing powder or water spray. Fight larger fires with water spray. |                       |  |
| firefighters:   A respiratory protective device may be necessary.     6 Accidential release measures     Personal precautions, protective<br>equipment and emergency<br>procedures:   Wear protective device against the effects of turnes/dust/aerosol.     Wethods and material for<br>containment and cleaning up:   Ensure adequate venitlation.     7 Handling and storage<br>Precautions for safe handling<br>Storage requirements:   Use only in vell venitlated areas.     8 Exposure controls/personal protection   Use only in vell venitlated areas.     7 Handling and storage<br>Precautions for safe handling<br>Storage requirements:   Use only in vell venitlated areas.     7 Barboure controls/personal protection   Components with limit values that require monitoring at the workplace:<br>67-84-1 Acetone     7 Hauding and storage<br>PrecL (USA)   Long-term value: 2400 mg/m <sup>2</sup> , 1000 ppm<br>RetL (USA)   Long-term value: 1000 mg/m <sup>2</sup> , 1000 ppm<br>RetL (USA)     17 V (USA)   Long-term value: 1000 mg/m <sup>2</sup> , 1000 ppm<br>RetL (USA)   Long-term value: 1000 mg/m <sup>2</sup> , 1000 ppm<br>RetL (USA)     17 V (USA)   Long-term value: 1000 mg/m <sup>2</sup> , 1000 ppm<br>RetL (USA)   Long-term value: 1000 mg/m <sup>2</sup> , 1000 ppm<br>RetL (USA)     17 V (USA)   Long-term value: 1000 mg/m <sup>2</sup> , 1000 ppm<br>RetL (USA)   Long-term value: 100 mg/m <sup>2</sup> , 100 ppm<br>RetL (USA)     17 V (USA)   Long-term value: 100 mg/m <sup>2</sup> , 100 ppm<br>RetL (USA)   Long-term value: 100 mg/m <sup>2</sup> , 100 ppm<br>RetL (USA)  |                                       |                          | Can form explosive gas-air mixtures.   |                       |  |
| A Acidential release measures Personal proceutions, protective quipment and demergency procedures: Wear protective equipment, Keep unprotected persons away, Use respiratory protective device against the effects of turnes/dust/aerosol. Ensure adequate ventilation. Thadling and storage Precations for safe handling Use only in well ventilated areas. Storage requirements: Use controls/personal protection Components with limit values that require monitoring at the workplace: <b>74-64 74-64</b>   | firefighters:                         | luipment ioi             | A respiratory protective device may be necessary.                              |                       |  |
| Personal precautions, protective<br>equipment and emergency<br>procedures:     Wear protective equipment. Keep unprotected persons away.<br>Use respiratory protective device against the effects of funesidustaerosol.       7 Handling and storage<br>Precoutions for safe handling<br>Storage requirements:     Les only in well ventilation.       7 Handling and storage<br>Precoutions for safe handling<br>Storage requirements:     Les only in well ventilated anse.<br>Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing<br>conditions. Store locked up.       8 Exposure controls/personal protection<br>Components with limit values that require monitoring at the workplace:<br>67-64+1 Acotone<br>PEL (USA)<br>Long-term value: 2400 mg/m?, 1000 ppm<br>REL (USA)<br>Long-term value: 1782 NIC-197 mg/m (500) NIC-2500 ppm<br>BEI<br>TV (USA)     Pet Lockal<br>Long-term value: 1800 mg/m?, 1000 ppm<br>REL (USA)       10 Geyr 6 no-butane<br>REL (USA)     Long-term value: 1800 mg/m?, 1000 ppm<br>REL (USA)     Long-term value: 1800 mg/m?, 1000 ppm<br>REL (USA)       10 Geyr 6 no-butane<br>REL (USA)     Long-term value: 1900 mg/m?, 800 ppm<br>REL (USA)     Long-term value: 1900 mg/m?, 800 ppm<br>REL (USA)       10 Geyr 7 A bartum sulfate, natural<br>REL (USA)     Long-term value: 1900 mg/m?, 800 ppm<br>REL (USA)     Long-term value: 1900 mg/m?, 800 ppm<br>REL (USA)       10 Geyr 7 Abartum sulfate, natural<br>REL (USA)     Long-term value: 1900 mg/m?, 800 ppm<br>REL (USA)     Long-term value: 1900 mg/m?, 800 ppm<br>REL (USA)       10 Geyr 6 no-term value: 1900 mg/m?, 800 ppm<br>REL (USA)     Long-term value: 190 mg/m?, 100 ppm<br>REL (USA)     Rem reprirate fraction<br>REL   |                                       |                          |  |                       |  |
| equipment and emergency<br>procedures:<br>Webhods and material for<br>containment and cleaning up:<br>Ensure adequate ventilation.<br>7 Handling and storage<br>Precuuions for safe handling<br>Storage requirements:<br>Use only in well ventilated areas.<br>Storage requirements:<br>0 Components with limit values that require monitoring at the workplace:<br>74-94-1 Acetone<br>74-94-1 Acetone<br>74-1 Acetone<br>75-1 Acetone<br>75-1 Aceton      | 6 Accidental                          | release measures         |  |                       |  |
| procedures:     Wear protective equipment. Keep unprotected persons away,<br>Use transment and cleaning up:     Use any in well ventilation.       7 Handling and storage<br>Precautions for safe handling<br>Storage requirements:     Use only in well ventilated areas.<br>Storage requirements:     Use only in well ventilated areas.<br>Storage requirements:       8 Exposure controls/personal protection     Components with limit values that require monitoring at the workplace:     67.44.4 Acetone       PEL (USA)     Long-term value: 2400 mg/m², 1000 ppm     PEL (USA)     Long-term value: 2400 mg/m², 1000 ppm       TU (USA)     Long-term value: 2400 mg/m², 1000 ppm     PEL (USA)     Long-term value: 1000 mg/m², 1000 ppm       TU (USA)     Long-term value: 1000 mg/m², 1000 ppm     PEL (USA)     Long-term value: 1000 mg/m², 1000 ppm       TU (USA)     Long-term value: 1000 mg/m², 1000 ppm     PEL (USA)     Long-term value: 2300 mg/m², 1000 ppm       TU (USA)     Long-term value: 1900 mg/m³, 1000 ppm     PEL (USA)     Long-term value: 1900 mg/m³, 1000 ppm       TU (USA)     Long-term value: 1900 mg/m³, 1000 ppm     PEL (USA)     Long-term value: 1900 mg/m³, 1000 ppm       TU (USA)     Long-term value: 1900 mg/m³, 1000 ppm     PEL (USA)     Long-term value: 1900 mg/m³, 1000 ppm       TU (USA)     Long-term value: 1900 mg/m³, 1000 ppm     PEL (USA) </th <th></th> <th></th> <th></th> <th></th>  |                                       |                          |  |                       |  |
| Methods and material for<br>containment and cleaning up:     Ensure adequate ventilation.       7 Handling and storage<br>Precautions for safe handling<br>Storage requirements:     Use only in well ventilated areas.<br>Storage requirements:     Use only in well ventilated areas.<br>Conditions. Store locked up.       8 Exposure controls/personal protection     Components with limit values that require monitoring at the workplace:<br>Components with limit values that require monitoring at the workplace:<br>Components with limit values that require monitoring at the workplace:<br>Components with limit values that require monitoring at the workplace:<br>Components with limit values that require monitoring at the workplace:<br>Components with limit values that require monitoring at the workplace:<br>Components with limit values that require monitoring at the workplace:<br>Components with limit values that require monitoring at the workplace:<br>Components with limit values that require monitoring at the workplace:<br>Components with limit values that require monitoring at the workplace:<br>Components with limit values that require monitoring at the workplace:<br>Components with limit values that require monitoring at the workplace:<br>Components with limit values that require monitoring at the workplace:<br>Component walue: (1782) NIC-187 mg/m (750) NIC-500 ppm<br>Etcl (USA) Long-term value: 1900 mg/m <sup>2</sup> , 1000 ppm<br>TLV (USA) Long-term value: 1900 mg/m <sup>2</sup> , 1000 ppm<br>TLV (USA) Short-term value: 1900 mg/m <sup>2</sup> , 1000 ppm<br>TLV (USA) Long-term value: 1900 mg/m <sup>2</sup> , 1000 ppm<br>TLV (USA) Long-term value: 1900 mg/m <sup>2</sup> , 1000 ppm<br>TLV (USA) Long-term value: 1900 mg/m <sup>2</sup> , 200 ppm<br>Etcl (USA) Long-term value: 200 mg/m <sup>2</sup> , 200 ppm<br>Etcl (USA) Long-term value: 200 mg/m <sup>2</sup> , 200 ppm<br>TLV (USA) Short-term value: 300 mg/m <sup>2</sup> , 200 ppm<br>Etcl (USA) Long-term value: 300 mg/m <sup>2</sup> , 200 ppm<br>Etcl (USA) Long-term value: 300 mg/m <sup>2</sup> , 200 ppm<br>TLV (USA) Short-term value: 300 mg/m <sup>2</sup> ,   |                                       | nd emergency             | Wear protective equipment. Keep upprotected persons away                       |                       |  |
| Containment and cleaning up:     Ensure adequate ventilation.       7 Handling and storage       Precoutions for safe handling<br>Storage requirements:     Les only in well ventilated areas.<br>Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing<br>conditions. Store locked up.       8 Exposure controls/personal protection       Components with limit values that require monitoring at the workplace:       67-64-1 Acetone       Precuse of the stand direct sunlight. Do not warehouse in subfreezing<br>conditions. Store locked up.       Storage requirem value: 2400 mg/m <sup>2</sup> , 1000 ppm       Ret. USA)     Long-term value: 2400 mg/m <sup>2</sup> , 1000 ppm       TV (VSA)     Storage maile: 1480 mg/m <sup>2</sup> , 1000 ppm       TV (VSA)     Long-term value: 1000 mg/m <sup>2</sup> , 1000 ppm       TV (VSA)     Long-term value: 1900 mg/m <sup>2</sup> , 1000 ppm       TV (VSA)     Long-term value: 1900 mg/m <sup>2</sup> , 1000 ppm       TV (VSA)     Long-term value: 1900 mg/m <sup>2</sup> , 800 ppm       TV (VSA)     Long-term value: 1900 mg/m <sup>2</sup> , 800 ppm       TV (VSA)     Long-term value: 1900 mg/m <sup>2</sup> , 800 ppm       TV (VSA)     <   | •                                     |                          | Use respiratory protective device against the effects of fumes/dust/aerosol.   |                       |  |
| 7 Handling and storage<br>Brozeutions for safe handling<br>Storage requirements:   Use only in well ventilated arease.<br>Sconditions. Store locked up.     8 Exposure controls/personal protection   Components with limit values that require monitoring at the workplace:   0     67-64-1 Acctine   Components with limit values that require monitoring at the workplace:   0     74-84-0 Acctine   Components with limit values for grim? 250 ppm<br>TLV (USA)   Long-term value: 2400 mg/m² 1000 ppm<br>REL (USA)   Long-term value: 1780 NLC-1187 mg/m² (750) NLC-500 ppm<br>BEI     74-84-6 propane   PEL (USA)   Long-term value: 1800 mg/m² 1000 ppm<br>REL (USA)   Long-term value: 1800 mg/m² 1000 ppm<br>REL (USA)   Long-term value: 1800 mg/m² 1000 ppm     7727-43-7 batima sufface, natural   PEL (USA)   Long-term value: 1900 mg/m³ 1000 ppm     7727-43-7 batima sufface, natural   PEL (USA)   Long-term value: 1900 mg/m³ 1000 ppm     7727-43-7 batima sufface, natural   PEL (USA)   Long-term value: 1900 mg/m³ 100 ppm     7727-43-7 batima sufface, natural   PEL (USA)   Long-term value: 1900 mg/m³ 100 ppm     710-84-7 batima sufface, natural   PEL (USA)   Long-term value: 300 mg/m³ 100 ppm     710-77-77-77-77-77-77-77-77-77-77-77-77-77   |                                       |                          | Ensure adequate ventilation  |                       |  |
| Precutions for safe handling<br>Storage requirements:     Use only in well ventilated areas.<br>Scep away from sources of heat and direct sunlight. Do not warehouse in subfreezing<br>conditions. Store locked up.       8 Exposure controls/personal protection   | containment                           | and cleaning up.         |  |                       |  |
| Precutions for safe handling<br>Storage requirements:     Use only in well ventilated areas.<br>Scep away from sources of heat and direct sunlight. Do not warehouse in subfreezing<br>conditions. Store locked up.       8 Exposure controls/personal protection   | 7 Handling an                         | nd storage               |  |                       |  |
| Storage requirements:     Keep alway from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions. Store tocked up.       8 Exposure controls/personal protection       Components with limit values that require monitoring at the workplace:       67-64-1 Acctone       PEL (USA)     Long-term value: 2400 mg/m³, 1000 ppm       REL (USA)     Long-term value: 71800 mg/m³, 2500 ppm       TV (USA)     Short-term value: (1180) NIC-1187 mg/m³ (750) NIC-250 ppm       BEI     PEL (USA)     Long-term value: 1800 mg/m³, 1000 ppm       REL (USA)     Long-term value: 1800 mg/m³, 1000 ppm     PEL (USA)     Long-term value: 1300 mg/m³, 1000 ppm       TV (USA)     Indep-term value: 1300 mg/m³, 1000 ppm     PEL (USA)     Long-term value: 2370 mg/m³, 1000 ppm       TV (USA)     Short-term value: 3270 mg/m³, 1000 ppm     PEL (USA)     Long-term value: 3270 mg/m³, 100 ppm       TV (USA)     Long-term value: 55 °m mg/m³     Total dust "respirable fraction     PEL (USA)     Long-term value: 300 mg/m³, 100 ppm       RL (USA)     Long-term value: 300 mg/m³, 100 ppm     PEL (USA)     Long-term value: 300 mg/m³, 100 ppm       RL (USA)     Long-term value: 300 mg/m³, 50 ppm     Tot dust "respirable fraction; E     PEL (USA)     Long-term value: 300 mg/m³, 100 ppm   |                                       |                          | Use only in well ventilated areas.   |                       |  |
| 8 Exposure controls/personal protection       Components with limit values that require monitoring at the workplace:       67-64-1 Acetone       PEL (USA)     Long-term value: 2400 mg/m <sup>3</sup> , 1000 ppm       REL (USA)     Long-term value: 7200 ppm       TV (USA)     Short-term value: 718.000 ppm       TV (USA)     Long-term value: 718.000 ppm       REL (USA)     Long-term value: 718.000 ppm       REL (USA)     Long-term value: 718.000 mg/m <sup>3</sup> , 1000 ppm       REL (USA)     Long-term value: 718.000 mg/m <sup>3</sup> , 1000 ppm       TV (USA)     Short-term value: 719.000 mg/m <sup>3</sup> , 800 ppm       TV (USA)     Long-term value: 719.000 mg/m <sup>3</sup> , 800 ppm       TV (USA)     Long-term value: 719.000 mg/m <sup>3</sup> , 800 ppm       TV (USA)     Short-term value: 719.5° mg/m <sup>3</sup> Total dust respirable fraction     Teach       TV (USA)     Long-term value: 719.5° mg/m <sup>3</sup> Total dust respirable fraction     Teach       TV (USA)     Long-term value: 75 mg/m <sup>3</sup> Total dust respirable fraction     Teach       TV (USA)     Long-term value: 50 mg/m <sup>3</sup> , 75 ppm       Long-term value: 50 mg/m <sup>3</sup> , 50 ppm     Teach       TV (USA)     Short-term value: 307 mg/m <sup>3</sup>   |                                       |                          | Keep away from sources of heat and direct sunlight. Do not warehou             | se in subfreezing     |  |
| Components with limit values that require monitoring at the workplace:<br>67-641 Acotone        PEL (USA)     Long-term value: 2400 mg/m³, 250 ppm<br>PEL (USA)     Long-term value: 2700 mg/m³, 250 ppm<br>Prescription (1180)          Bort-term value: (1782) NIC-1187 mg/m³, (750) NIC-500 ppm<br>BEI term value: (1782) NIC-1187 mg/m³, (500) NIC-250 ppm<br>BEI (USA)     Long-term value: 1800 mg/m³, 1000 ppm<br>REL (USA)     Long-term value: 1800 mg/m³, 1000 ppm<br>REL (USA)     Long-term value: 1800 mg/m³, 1000 ppm<br>TLV (USA)     Indeg-term value: 1800 mg/m³, 1000 ppm<br>TLV (USA)     Indeg-term value: 1900 mg/m³, 800 ppm<br>TLV (USA)     Indeg-term value: 1900 mg/m³, 800 ppm<br>TLV (USA)     Indeg-term value: 1900 mg/m³, 800 ppm<br>TLV (USA)     Indeg-term value: 2370 mg/m³, 1000 ppm<br>TT777-437-Tbar/m sultificte, natural<br>PEL (USA)     Long-term value: 2070 mg/m³, 1000 ppm<br>TtV (USA)     Indeg-term value: 2070 mg/m³, 1000 ppm<br>REL (USA)     Long-term value: 207 mg/m³<br>'total dust respirable fraction term value: 200 mg/m³, 100 ppm<br>REL (USA)     Long-term value: 307 mg/m³, 100 ppm<br>REL (USA)     Long-term value: 307 mg/m³, 100 ppm<br>Long-term value: 307 mg/m³, 100 ppm<br>REL (USA)     Long-term value: 307 mg/m³, 100 ppm  |                                       |                          | conditions. Store locked up.   |                       |  |
| Components with limit values that require monitoring at the workplace:<br>67-641 Acotone        PEL (USA)     Long-term value: 2400 mg/m³, 250 ppm<br>PEL (USA)     Long-term value: 2700 mg/m³, 250 ppm<br>Prescription (1180)          Bort-term value: (1782) NIC-1187 mg/m³, (750) NIC-500 ppm<br>BEI term value: (1782) NIC-1187 mg/m³, (500) NIC-250 ppm<br>BEI (USA)     Long-term value: 1800 mg/m³, 1000 ppm<br>REL (USA)     Long-term value: 1800 mg/m³, 1000 ppm<br>REL (USA)     Long-term value: 1800 mg/m³, 1000 ppm<br>TLV (USA)     Indeg-term value: 1800 mg/m³, 1000 ppm<br>TLV (USA)     Indeg-term value: 1900 mg/m³, 800 ppm<br>TLV (USA)     Indeg-term value: 1900 mg/m³, 800 ppm<br>TLV (USA)     Indeg-term value: 1900 mg/m³, 800 ppm<br>TLV (USA)     Indeg-term value: 2370 mg/m³, 1000 ppm<br>TT777-437-Tbar/m sultificte, natural<br>PEL (USA)     Long-term value: 2070 mg/m³, 1000 ppm<br>TtV (USA)     Indeg-term value: 2070 mg/m³, 1000 ppm<br>REL (USA)     Long-term value: 207 mg/m³<br>'total dust respirable fraction term value: 200 mg/m³, 100 ppm<br>REL (USA)     Long-term value: 307 mg/m³, 100 ppm<br>REL (USA)     Long-term value: 307 mg/m³, 100 ppm<br>Long-term value: 307 mg/m³, 100 ppm<br>REL (USA)     Long-term value: 307 mg/m³, 100 ppm  | 9 Evnes                               | ontrolo/noroonal and     |  |                       |  |
| 67-64-1     Acetone       PEEL (USA)     Long-term value: 2400 mg/m <sup>3</sup> , 1000 ppm       REL (USA)     Long-term value: 590 mg/m <sup>3</sup> , 250 ppm       TV (USA)     Short-term value: (1186; NIC-594 mg/m <sup>3</sup> , (500) NIC-500 ppm       BEI     PEE (USA)       Long-term value: (1186; NIC-594 mg/m <sup>3</sup> , (500) NIC-500 ppm       BEI     Degreem value: (1186; NIC-594 mg/m <sup>3</sup> , (500) NIC-500 ppm       PEL (USA)     Long-term value: 1800 mg/m <sup>3</sup> , 1000 ppm       TV-V (USA)     Long-term value: 1800 mg/m <sup>3</sup> , 1000 ppm       TV-V (USA)     Short-term value: 1300 mg/m <sup>3</sup> , 1000 ppm       TV-V (USA)     Short-term value: 1300 mg/m <sup>3</sup> , 1000 ppm       TV-V (USA)     Short-term value: 1300 mg/m <sup>3</sup> , 1000 ppm       TV-V (USA)     Short-term value: 1300 mg/m <sup>3</sup> , 1000 ppm       TV-V (USA)     Short-term value: 1300 mg/m <sup>3</sup> Long-term value: 130 mg/m <sup>3</sup> , 1000 ppm       REL (USA)     Long-term value: 140 mg/m <sup>3</sup> TV-V (USA)     Short-term value: 205 mg/m <sup>3</sup> Short-term value: 205 mg/m <sup>3</sup> 100 ppm       PEL (USA)     Long-term value: 300 mg/m <sup>3</sup> , 750 ppm       Long-term value: 205 mg/m <sup>3</sup> , 200 ppm       REL (USA)     Long-term value: 205 mg/m <sup>3</sup> , 100 ppm       R  |                                       |                          |  |                       |  |
| PEL (USA)     Long-term value: 2400 mg/m <sup>2</sup> , 1000 ppm       REL (USA)     Long-term value: (1782) NIC-1187 mg/m <sup>2</sup> , (750) NIC-500 ppm       Del <sup>+</sup> erm value: (1782) NIC-1187 mg/m <sup>2</sup> , (750) NIC-500 ppm     Bel <sup>+</sup> erm value: (1782) NIC-1187 mg/m <sup>2</sup> , (750) NIC-500 ppm       PEL (USA)     Long-term value: 1800 mg/m <sup>2</sup> , 1000 ppm     Rest       TV-USA)     Long-term value: 1800 mg/m <sup>2</sup> , 1000 ppm     Rest       TV (USA)     Long-term value: 1800 mg/m <sup>2</sup> , 1000 ppm     Rest       TV-U (USA)     Long-term value: 1900 mg/m <sup>2</sup> , 800 ppm     TV/V (USA)       Short-term value: 2370 mg/m <sup>2</sup> , 1000 ppm     TV/V (USA)     Long-term value: 100 mg/m <sup>2</sup> , 1000 ppm       TVZ-74-37 Parium sulfate, natural     PEL     Test on the sulfate natural     Test on the sulfate natural       PEL (USA)     Long-term value: 10° 5 <sup>**</sup> mg/m <sup>3</sup> 1000 ppm     Test on the sulfate natural       TV-V (USA)     Short-term value: 300 mg/m <sup>3</sup> , 75 ppm     Total dust     Test on the sulfate natural       TV-V (USA)     Short-term value: 205 mg/m <sup>3</sup> , 50 ppm     Tucl dust     Short-term value: 205 mg/m <sup>3</sup> , 100 ppm       TV-V (USA)     Short-term value: 300 mg/m <sup>3</sup> , 75 ppm     Tucl dust     Test dust       Short-term value: 205 mg/m <sup>3</sup> , 150 ppm     Long-term value: 205 mg/m <sup>3</sup> , 150 ppm<  | •                                     |                          | equire monitoring at the workplace:  |                       |  |
| REL (USA)   Long-term value: 590 mg/m <sup>2</sup> , 250 ppm     TLV (USA)   Short-term value: (1188) NIC-594 mg/m <sup>2</sup> , (500) NIC-500 ppm     BEI   Digeterm value: (1188) NIC-594 mg/m <sup>2</sup> , (500) NIC-250 ppm     PEL (USA)   Long-term value: 1800 mg/m <sup>2</sup> , 1000 ppm     REL (USA)   Long-term value: 1800 mg/m <sup>2</sup> , 1000 ppm     TV-V (USA)   refer to Appendix F     106-97-9 n-butane   Image: 1900 mg/m <sup>2</sup> , 1000 ppm     REL (USA)   Long-term value: 1900 mg/m <sup>2</sup> , 800 ppm     TV-V (USA)   Short-term value: 1907 mg/m <sup>2</sup> , 1000 ppm     TV-V (USA)   Short-term value: 197 of mg/m <sup>2</sup> , 1000 ppm     TV-V (USA)   Short-term value: 197 s <sup>++</sup> mg/m <sup>2</sup> Total du's "respirable fraction   Tetal du's "respirable fraction     TV-V (USA)   Long-term value: 17 s <sup>++</sup> mg/m <sup>2</sup> Tribal du's "respirable fraction   Tetal du's "respirable fraction     TV-V (USA)   Long-term value: 17 s <sup>++</sup> mg/m <sup>2</sup> Tribal du's "respirable fraction   Tetal du's "respirable fraction     TV-V (USA)   Long-term value: 17 s <sup>++</sup> mg/m <sup>2</sup> Tribal du's "respirable fraction   Tetal du's "respirable fraction     LONg-term value: 300 mg/m <sup>3</sup> , 100 ppm   Tetal du's "respirable fraction     LONg-term value: 300 mg/m <sup>3</sup> , 200 ppm   EI <th></th> <th></th> <th>ng/m³ 1000 ppm</th> <th></th>  |                                       |                          | ng/m³ 1000 ppm   |                       |  |
| TLV (USA)   Short-term value: (1782) NIC-1187 mg/m³, (500) NIC-500 ppm<br>Ent     PEL   USA)   Long-term value: 11800 mg/m³, 1000 ppm     PEL   USA)   Long-term value: 1800 mg/m³, 1000 ppm     REL   USA)   Long-term value: 1800 mg/m³, 1000 ppm     TLV   UUSA)   Long-term value: 1900 mg/m³, 1000 ppm     TLV   UUSA)   Long-term value: 2370 mg/m³, 1000 ppm     TV2V-437   Darg-term value: 1900 mg/m³, 800 ppm     TV2V-437   Darg-term value: 15° 5°* mg/m³     *total dust *respriable fraction   REL     REL   USA)   Long-term value: 15° 5°* mg/m³     *total dust *respriable fraction   TVV     REL   USA)   Long-term value: 10° 5°* mg/m³     *total dust *respriable fraction   TVV     TVV   USA)   Long-term value: 5° mg/m³     *total dust *respriable fraction   E     TVV   USA)   Long-term value: 500 mg/m³, 75 ppm     Long-term value: 200 mg/m³, 75 ppm   Long-term value: 200 mg/m³, 75 ppm     Long-term value: 200 mg/m³, 100 ppm   TVV     TVV   USA)   Long-term value: 200 mg/m³, 150 ppm     TVV   USA)   Long-term value: 300 mg/m³, 150 ppm <th></th> <th></th> <th></th> <th></th>  |                                       |                          |  |                       |  |
| BEI <sup>+</sup> Test to the second   |                                       | Short-term value: (1782) | NIC-1187 mg/m <sup>3</sup> , (750) NIC-500 ppm                                 |                       |  |
| 74-98-6 propane       PEL (USA)     Long-term value: 1800 mg/m³, 1000 ppm       REL (USA)     Long-term value: 1800 mg/m³, 1000 ppm       TUV (USA)     Inder to Appendix F       106-97-8 h-butane     REL (USA)       REL (USA)     Long-term value: 300 mg/m³, 800 ppm       TVZV-43-7 barium sulfate, natural     PEL (USA)       PEL (USA)     Long-term value: 307 mg/m³, 800 ppm       TVZV-47-7 barium sulfate, natural     PEL (USA)       Long-term value: 10* 5** mg/m³     "total dust "respirable fraction       REL (USA)     Long-term value: 6* mg/m³       'total dust "respirable fraction     "total dust "respirable fraction       TLV (USA)     Short-term value: 300 mg/m³, 100 ppm       PEL (USA)     Long-term value: 300 mg/m³, 75 ppm       LOg-term value: 300 mg/m³, 75 ppm     Long-term value: 300 mg/m³, 50 ppm       TLV (USA)     Short-term value: 300 mg/m³, 100 ppm       REL (USA)     Long-term value: 700 mg/m³, 150 ppm       TLV (USA)     Long-term value: 530 mg/m³, 150 ppm       TLV (USA)     Long-term value: 630 mg/m³, 150 ppm       TLV (USA)     Long-term value: 435 mg/m³, 150 ppm       TLV (USA)     Short-term value: 435 mg/m³, 150 ppm  |                                       | Long-term value: (1188)  | NIC-594 mg/m³, (500) NIC-250 ppm   |                       |  |
| PEL (USA)   Long-term value: 1800 mg/m³, 1000 ppm     REL (USA)   Long-term value: 1800 mg/m³, 1000 ppm     TLV (USA)   Iong-term value: 1900 mg/m³, 800 ppm     TLV (USA)   Long-term value: 1900 mg/m³, 1000 ppm     7727-437-brainum sultifate, natural   Trest (USA)     PEL (USA)   Long-term value: 1905 "mg/m³     106-97.8   hours (If a constraint)     7727-437-brainum sultifate, natural   Trespirable fraction     7727-437   trait dust "respirable fraction     108-10-1   trespirable fraction     11V (USA)   Long-term value: 10° 5°" mg/m³     11V (USA)   Long-term value: 10° 5°" mg/m³     11V (USA)   Long-term value: 10° 5° mg/m³     11V (USA)   Long-term value: 10° 5° mg/m³     11V (USA)   Long-term value: 10° 5° mg/m³     11V (USA)   Long-term value: 205 mg/m³, 50 ppm     12V (USA)   Short-term value: 205 mg/m³, 200 ppm     12V (USA)   Long-term value: 300 mg/m³, 200 ppm     12V (USA)   Long-term value: 300 mg/m³, 200 ppm     1300-20-7 xylene (mix)   Trespirable fraction     1302-02-7 xylene (mix)   Trespirable fraction     1213-02-02-7 xylene (mix)   Trespirable fraction </th <th>74-98-6 prop</th> <th></th> <th></th> <th></th>  | 74-98-6 prop                          |                          |  |                       |  |
| REL (USA)   Long-term value: 1800 mg/m³, 1000 ppm     TLV (USA)   refer to Appendix F <b>106-97-8 n-butane</b> REL (USA)     REL (USA)   Long-term value: 2370 mg/m³, 800 ppm <b>TVLV (USA)</b> Short-term value: 2370 mg/m³, 1000 ppm <b>7727-43-7 barium sulfate, natural</b> PEL (USA)     PEL (USA)   Long-term value: 15° 5** mg/m³     *total dust "respirable fraction     REL (USA)   Long-term value: 5° mg/m³     *total dust "respirable fraction     TLV (USA)   Long-term value: 5° mg/m³     *total dust "respirable fraction     TLV (USA)   Long-term value: 5° mg/m³     *total dust "respirable fraction     TLV (USA)   Long-term value: 300 mg/m³, 100 ppm     REL (USA)   Long-term value: 300 mg/m³, 75 ppm     L (USA)   Short-term value: 205 mg/m³, 20 ppm     BEI <b>107-87-9 Methyl Propyl Ketone PEI</b> (USA)   Long-term value: 700 mg/m³, 20 ppm     BEI <b>108-10-1erm</b> value: 700 mg/m³, 200 ppm <b>110-19: CuSA</b> Long-term value: 700 mg/m³, 100 ppm <b>120: CuSA</b> Long-term value: 700 mg/m³, 100 ppm     REL (USA)   Long-term value: 435 mg/m³, 100 ppm <b>1303-02</b>  |                                       |                          | ng/m <sup>3</sup> , 1000 ppm   |                       |  |
| 106-97-8 n-butane       REL (USA)     Long-term value: 1900 mg/m³, 800 ppm       TLV (USA)     Short-term value: 2370 mg/m³, 1000 ppm       7727-43-7 barium sulfate, natural     PEL (USA)       PEL (USA)     Long-term value: 15* 5** mg/m³       'total dust *respirable fraction     'total dust *respirable fraction       TLV (USA)     Long-term value: 5 mg/m³       'total dust *respirable fraction     Long-term value: 5 mg/m³       TLV (USA)     Long-term value: 410 mg/m³, 100 ppm       Short-term value: 300 mg/m³, 75 ppm     Long-term value: 300 mg/m³, 75 ppm       Long-term value: 300 mg/m³, 75 ppm     Long-term value: 307 mg/m³, 200 ppm       TLV (USA)     Short-term value: 307 mg/m³, 75 ppm       Long-term value: 300 mg/m³, 200 ppm     EL (USA)       Long-term value: 300 mg/m³, 200 ppm       TLV (USA)     Long-term value: 700 mg/m³, 200 ppm       TLV (USA)     Long-term value: 700 mg/m³, 150 ppm       TLV (USA)     Long-term value: 700 mg/m³, 100 ppm       REL (USA)     Long-term value: 435 mg/m³, 100 ppm       TLV (USA)     Short-term value: 435 mg/m³, 100 ppm       REL (USA)     Long-term value: 435 mg/m³, 100 ppm       REL (USA)     Short-term value: 43  |                                       | Long-term value: 1800 r  |  |                       |  |
| REL (USA)   Long-term value: 1900 mg/m³, 800 ppm     TLV (USA)   Short-term value: 2370 mg/m³, 1000 ppm <b>7727-43-7 barium sulfate, natural</b> PEL (USA)   Long-term value: 15* 5** mg/m³     *total dust **respirable fraction     REL (USA)   Long-term value: 10* 5** mg/m³     *total dust **respirable fraction     TLV (USA)   Long-term value: 5* mg/m³     *total dust **respirable fraction     TLV (USA)   Long-term value: 5* mg/m³     *total dust **respirable fraction     *total dust **respirable fraction     PEL (USA)   Long-term value: 410 mg/m³, 100 ppm     REL (USA)   Short-term value: 307 mg/m³, 75 ppm     Long-term value: 307 mg/m³, 75 ppm     Long-term value: 307 mg/m³, 75 ppm     Long-term value: 307 mg/m³, 75 ppm     BEI <b>107-87-9 Methyl Propyl Ketone</b> PEL (USA)   Long-term value: 520 mg/m³, 150 ppm     TLV (USA)   Short-term value: 520 mg/m³, 150 ppm <b>1330-20-7 xylene (mix)</b> PEL (USA)   Long-term value: 435 mg/m³, 100 ppm     REL (USA)   Short-term value: 655 mg/m³, 150 ppm     Long-term value: 655 mg/m³, 150 ppm     Long-term value: 655 mg/m³, 150 ppm <th></th> <th></th> <th></th> <th></th>  |                                       |                          |  |                       |  |
| TLV (USA)   Short-term value: 2370 mg/m³, 1000 ppm     7727-43-7 barium sulfate, natural     PEL (USA)   Long-term value: 15" 5" mg/m³     *total dust *respirable fraction     REL (USA)   Long-term value: 10" 5" mg/m³     *total dust *respirable fraction     TLV (USA)   Long-term value: 5" mg/m³     *total dust *respirable fraction     TLV (USA)   Long-term value: 5" mg/m³     *infalable fraction; E     108-10-1 methyl isobutyl ketone     PEL (USA)   Long-term value: 400 mg/m³, 100 ppm     REL (USA)   Short-term value: 300 mg/m³, 75 ppm     Long-term value: 307 mg/m³, 75 ppm     Long-term value: 307 mg/m³, 75 ppm     Long-term value: 307 mg/m³, 150 ppm     BEI     107-87-9 Methyl Propyl Ketone     PEL (USA)     Long-term value: 500 mg/m³, 150 ppm     TLV (USA)   Short-term value: 500 mg/m³, 150 ppm     TLV (USA)   Short-term value: 435 mg/m³, 100 ppm     REL (USA)   Short-term value: 435 mg/m³, 100 ppm     REL (USA)   Short-term value: 435 mg/m³, 100 ppm     REL (USA)   Short-term value: 435 mg/m³, 100 ppm     Long-term value: 435 mg/m³, 100 ppm   Long-term value: 435 mg/m³, 100   |                                       |                          | ng/m3 000 nnm  |                       |  |
| 7727-43-7 barlum sulfate, natural     PEL (USA)   Long-term value: 10* 5** mg/m³  |                                       |                          |  |                       |  |
| *total dust **respirable fraction     REL (USA)   Long-term value: 10* 5** mg/m³<br>*total dust **respirable fraction     TLV (USA)   Long-term value: 5* mg/m³<br>*inhalable fraction; E <b>108-10-1 methyl isobutyl ketone</b> PEL (USA)   Long-term value: 300 mg/m³, 100 ppm     REL (USA)   Short-term value: 300 mg/m³, 75 ppm<br>Long-term value: 300 mg/m³, 75 ppm     TLV (USA)   Short-term value: 300 mg/m³, 75 ppm<br>Long-term value: 30 mg/m³, 75 ppm     BEI <b>107-87-9 Methyl Propyl Ketone</b> PEL (USA)   Long-term value: 700 mg/m³, 200 ppm     BEI <b>107-87-9 Methyl Propyl Ketone</b> PEL (USA)   Long-term value: 520 mg/m³, 150 ppm     TLV (USA)   Short-term value: 529 mg/m³, 150 ppm     TLV (USA)   Short-term value: 435 mg/m³, 100 ppm     REL (USA)   Long-term value: 435 mg/m³, 100 ppm     TLV (USA)   Short-term value: 655 mg/m³, 150 ppm     Dep-term value: 435 mg/m³, 150 ppm   Long-term value: 435 mg/m³, 150 ppm     TLV (USA)   Short-term value: 655 mg/m³, 150 ppm     BEI <b>108-65-6 PM acetate</b> WEEL (USA)   Long-term value: 50 ppm <b>110-19-0 isobutyl acetate W</b> PEL (USA)   Long-term value: 50 ppm <b>110-19-0 i</b>   |                                       |                          |  |                       |  |
| REL (USA)   Long-term value: 10* 5** mg/m³<br>*total dust **respirable fraction<br>total dust **respirable fraction     TLV (USA)   Long-term value: 5* mg/m³<br>*inhalable fraction; E <b>108-10-1 metryl isobutyl ketone</b> PEL (USA)   Long-term value: 410 mg/m³, 100 ppm     REL (USA)   Short-term value: 300 mg/m³, 75 ppm<br>Long-term value: 307 mg/m³, 75 ppm<br>Long-term value: 307 mg/m³, 75 ppm     TLV (USA)   Short-term value: 307 mg/m³, 75 ppm     Long-term value: 307 mg/m³, 700 ppm     REL (USA)   Long-term value: 435 mg/m³, 100 ppm     TLV (USA)   Short-term value: 655 mg/m³, 150 ppm     Long-term value: 435 mg/m³, 100 ppm     REL (USA)   Short-term value: 434 mg/m³, 100 ppm     BEI <b>108-65-6 PM acetate</b> WEEL (USA)   Long-term value: 50 ppm <b>110-19-0 isobutyl acetate</b> PEL (USA)  |                                       | Long-term value: 15* 5*  | * mg/m³  |                       |  |
| *totāl dust **respirable fraction     TLV (USA)   Long-term value: 5* mg/m³     *inhalable fraction; E <b>108-10-1 methyl isobutyl ketone</b> PEL (USA)   Long-term value: 300 mg/m³, 75 ppm     Long-term value: 205 mg/m³, 56 ppm     Long-term value: 307 mg/m³, 75 ppm     Long-term value: 307 mg/m³, 70 ppm     BEI <b>107-87-9 Methyl Propyl Ketone</b> PEL (USA)     Long-term value: 700 mg/m³, 200 ppm     BEI <b>107-87-9 Methyl Propyl Ketone</b> PEL (USA)     Long-term value: 530 mg/m³, 150 ppm     TLV (USA)   Short-term value: 529 mg/m³, 150 ppm     TLV (USA)   Short-term value: 435 mg/m³, 100 ppm     PEL (USA)   Long-term value: 435 mg/m³, 100 ppm     Long-term value: 435 mg/m³, 150 ppm   Long-term value: 655 mg/m³, 150 ppm     Dong-term value: 655 mg/m³, 150 ppm   BEI <b>108-65-6 PM acetate</b> WEEL     WEEL (USA)   Long-term value: 50 ppm <b>110-19-0 isobutyl acetate</b> PEL (USA)     PEL (USA)   Long-term value: 700 mg/   |                                       |                          |  |                       |  |
| TLV (USA)   Long-term value: 5* mg/m³     108-10-1 methyl isobutyl ketone   PEL (USA)     Long-term value: 410 mg/m³, 100 ppm     REL (USA)   Short-term value: 300 mg/m³, 50 ppm     Long-term value: 307 mg/m³, 50 ppm     TLV (USA)   Short-term value: 307 mg/m³, 75 ppm     Long-term value: 307 mg/m³, 75 ppm     TLV (USA)   Long-term value: 500 ppm     REL (USA)   Long-term value: 520 mg/m³, 150 ppm     TLV (USA)   Long-term value: 435 mg/m³, 100 ppm     REL (USA)   Long-term value: 655 mg/m³, 100 ppm     Long-term value: 651 mg/m³, 100 ppm     Long-term value: 436 mg/m³, 100 ppm     BEI     108-65-6 PM acetate     WEEL (USA)   Long-term value: 50 ppm     HEL (USA)   Long-term value: 700 mg/m³, 150 ppm     PEL (USA)   Long-term value  | REL (USA)                             | Long-term value: 10° 5°  | raction  |                       |  |
| 'inhälable fraction; E     108-10-1 methyl isobutyl ketone     PEL (USA)   Long-term value: 410 mg/m³, 100 ppm     REL (USA)   Short-term value: 205 mg/m³, 50 ppm     Long-term value: 205 mg/m³, 50 ppm     TLV (USA)   Short-term value: 307 mg/m³, 75 ppm     Long-term value: 205 mg/m³, 50 ppm     BEI     107-87-9 Methyl Propyl Ketone     PEL (USA)     Long-term value: 700 mg/m³, 150 ppm     TLV (USA)     Short-term value: 529 mg/m³, 150 ppm     TLV (USA)     Short-term value: 629 mg/m³, 150 ppm     TLV (USA)     Short-term value: 435 mg/m³, 100 ppm     REL (USA)     Long-term value: 435 mg/m³, 100 ppm     REL (USA)     Long-term value: 655 mg/m³, 100 ppm     Long-term value: 435 mg/m³, 100 ppm     Drug-term value: 434 mg/m³, 100 ppm     BEI     108-65-6 PM acetate     WEEL (USA)   Long-term value: 50 ppm     LOng-term value: 50 ppm     110-19-0 isobutyl acetate     PEL (USA)   Long-term value: 700 mg/m³, 150 ppm     REL (USA)   Long-term value: 700 mg/m³, 150 ppm     REL (USA)   Long-term value: 700 mg/m³, 150  | TLV (USA)                             | Long-term value: 5* mg/  |  |                       |  |
| PEL (USA)Long-term value: 410 mg/m³, 100 ppmREL (USA)Short-term value: 300 mg/m³, 75 ppmLong-term value: 205 mg/m³, 50 ppmTLV (USA)Short-term value: 307 mg/m³, 75 ppmLong-term value: 82 mg/m³, 20 ppmBEI107-87-9 Methyl Propyl KetonePEL (USA)Long-term value: 700 mg/m³, 200 ppmREL (USA)Long-term value: 530 mg/m³, 150 ppmTLV (USA)Short-term value: 529 mg/m³, 150 ppmTLV (USA)Short-term value: 529 mg/m³, 150 ppm1330-20-7 xylene (mix)PEL (USA)Long-term value: 655 mg/m³, 100 ppmREL (USA)Short-term value: 655 mg/m³, 150 ppmLong-term value: 435 mg/m³, 100 ppmREL (USA)Short-term value: 651 mg/m³, 150 ppmLong-term value: 435 mg/m³, 100 ppmREL (USA)Short-term value: 651 mg/m³, 150 ppmLong-term value: 651 mg/m³, 150 ppmLong-term value: 651 mg/m³, 150 ppmLong-term value: 651 mg/m³, 100 ppmBEI108-65-6 PM acetateWEEL (USA)Long-term value: 50 ppm110-19-0 isobutyl acetatePEL (USA)Long-term value: 700 mg/m³, 150 ppmREL (USA)Long-term v   |                                       | *inhalable fraction; E   |  |                       |  |
| REL (USA)   Short-term value: 300 mg/m³, 75 ppm<br>Long-term value: 205 mg/m³, 50 ppm<br>BEI     TLV (USA)   Short-term value: 307 mg/m³, 20 ppm<br>BEI <b>107-87-9 Methyl Propyl Ketone</b> PEL (USA)   Long-term value: 700 mg/m³, 200 ppm<br>REL (USA)     Long-term value: 529 mg/m³, 150 ppm     TLV (USA)   Short-term value: 529 mg/m³, 150 ppm <b>1330-20-7 xylene (mix)</b> PEL (USA)   Long-term value: 435 mg/m³, 100 ppm     LOG-term value: 435 mg/m³, 100 ppm     REL (USA)   Long-term value: 655 mg/m³, 100 ppm     Long-term value: 435 mg/m³, 100 ppm     BEI <b>108-65-6 PM acetate</b> WEEL (USA)   Long-term value: 50 ppm <b>101-19-0 isobutyl acetate</b> WEEL (USA)   Long-term value: 700 mg/m³, 150 ppm     PEL (USA)   Long-term value: 700 mg/m³, 150 ppm     TUC (USA)   Long-term value: 700 mg/m³, 150 ppm     REL (USA)   Long-term value: 713 mg/m³, 150 ppm   |                                       | hyl isobutyl ketone      | a/m3 100 ppm   |                       |  |
| Long-term value: 205 mg/m³, 50 ppmTLV (USA)Short-term value: 307 mg/m³, 75 ppmLong-term value: 82 mg/m³, 20 ppmBEI107-87-9 Methyl Propyl KetonePEL (USA)Long-term value: 700 mg/m³, 200 ppmREL (USA)Long-term value: 530 mg/m³, 150 ppm1330-20-7 xylene (mix)PEL (USA)Long-term value: 529 mg/m³, 150 ppm1330-20-7 xylene (mix)PEL (USA)Long-term value: 435 mg/m³, 100 ppmREL (USA)Long-term value: 655 mg/m³, 150 ppmLong-term value: 435 mg/m³, 100 ppmREL (USA)Short-term value: 651 mg/m³, 150 ppmLong-term value: 434 mg/m³, 100 ppmBEI108-65-6 PM acetateWEEL (USA)Long-term value: 50 ppmPEL (USA)Long-term value: 50 ppmLong-term value: 700 mg/m³, 150 ppmREL (USA)Long-term value: 50 ppmTLV (USA)Long-term value: 700 mg/m³, 150 ppmRELUUSA)Long-term value: 700 mg/m³, 150 ppmTUV (USA)Long-term value: 700 mg/m³, 150 ppmTUV (USA)Long-term value: 700 mg/m³, 150 ppmREL(USA)Long-term value: 700 mg/m³, 150 ppmRELRELREL <t< th=""><th></th><th></th><th></th><th></th></t<>  |                                       |                          |  |                       |  |
| Long-term value: 82 mg/m³, 20 ppm<br>BEI107-87-9 Methyl Propyl KetonePEL (USA)Long-term value: 700 mg/m³, 200 ppm<br>Long-term value: 530 mg/m³, 150 ppmTLV (USA)Short-term value: 529 mg/m³, 150 ppm1330-20-7 xylene (mix)PEL (USA)Long-term value: 435 mg/m³, 100 ppmREL (USA)Short-term value: 655 mg/m³, 150 ppm<br>Long-term value: 655 mg/m³, 150 ppm<br>Long-term value: 655 mg/m³, 100 ppmTLV (USA)Short-term value: 655 mg/m³, 100 ppm<br>Long-term value: 434 mg/m³, 100 ppm<br>BEI108-65-6 PM acetateWEEL (USA)<br>Long-term value: 50 ppm<br>BEIPEL (USA)Long-term value: 50 ppm<br>Long-term value: 700 mg/m³, 150 ppm<br>Long-term value: 700 mg/m³, 150 ppm<br>Long-term value: 50 ppmTUV (USA)Long-term value: 700 mg/m³, 150 ppm<br>Long-term value: 700 mg/m³, 150 ppm<br>Long-term value: 700 mg/m³, 150 ppm<br>Long-term value: 700 mg/m³, 150 ppmTUV (USA)Long-term value: 700 mg/m³, 150 ppm<br>Long-term value: 700 mg/m³, 150 ppmTUV (USA)Long-term value: 700 mg/m³, 150 ppmTUV (USA)Long-term value: 700 mg/m³, 150 ppmREL (USA)Long-term value: 700 mg/m³, 150 ppm   |                                       | Long-term value: 205 m   | g/m³, 50 ppm   |                       |  |
| BEI   Intervention     107-87-9 Methyl Propyl Ketone     PEL (USA)   Long-term value: 700 mg/m³, 200 ppm     REL (USA)   Long-term value: 530 mg/m³, 150 ppm     TLV (USA)   Short-term value: 529 mg/m³, 150 ppm     1330-20-7 xylene (mix)   PEL (USA)     PEL (USA)   Long-term value: 435 mg/m³, 100 ppm     REL (USA)   Short-term value: 655 mg/m³, 150 ppm     Long-term value: 435 mg/m³, 100 ppm     REL (USA)   Short-term value: 651 mg/m³, 100 ppm     Long-term value: 651 mg/m³, 100 ppm     BEI     108-65-6 PM acetate     WEEL (USA)   Long-term value: 50 ppm     110-19-0 isobutyl acetate     PEL (USA)   Long-term value: 700 mg/m³, 150 ppm     REL (USA)   Long-term value: 700 mg/m³, 150 ppm     T10-19-0 isobutyl acetate   PEL (USA)     PEL (USA)   Long-term value: 700 mg/m³, 150 ppm     REL (USA)   Long-term value: 713 mg/m³, 150 ppm   | TLV (USA)                             | Short-term value: 307 m  | g/m³, 75 ppm   |                       |  |
| PEL (USA)     Long-term value: 700 mg/m³, 200 ppm       REL (USA)     Long-term value: 530 mg/m³, 150 ppm       TLV (USA)     Short-term value: 529 mg/m³, 150 ppm <b>1330-20-7 xylene (mix)</b> PEL (USA)     Long-term value: 435 mg/m³, 100 ppm       REL (USA)     Long-term value: 655 mg/m³, 150 ppm       Long-term value: 655 mg/m³, 150 ppm     Long-term value: 651 mg/m³, 100 ppm       TLV (USA)     Short-term value: 651 mg/m³, 100 ppm       TLV (USA)     Short-term value: 651 mg/m³, 100 ppm       BEI     Usa <b>108-65-6 PM acetate</b> WEEL (USA)     Long-term value: 50 ppm <b>101-19-0 isobutyl acetate</b> PEL (USA)     Long-term value: 700 mg/m³, 150 ppm       REL (USA)     Long-term value: 700 mg/m³, 150 ppm       TLV (USA)     Long-term value: 700 mg/m³, 150 ppm   |                                       |                          | m², 20 ppm   |                       |  |
| REL (USA)<br>TLV (USA)Long-term value: 530 mg/m³, 150 ppm <b>1330-20-7 xylene (mix)</b> PEL (USA)<br>REL (USA)Long-term value: 435 mg/m³, 100 ppm<br>Long-term value: 655 mg/m³, 150 ppm<br>Long-term value: 651 mg/m³, 100 ppmTLV (USA)Short-term value: 651 mg/m³, 100 ppm<br>BEI <b>108-65-6 PM acetate</b> WEEL (USA)Long-term value: 50 ppm<br>Long-term value: 50 ppm<br>BEI <b>101-19-0 isobutyl acetate</b> PEL (USA)Long-term value: 700 mg/m³, 150 ppm<br>Long-term value: 50 ppm <b>110-19-0 isobutyl acetate</b> PEL (USA)Long-term value: 700 mg/m³, 150 ppm<br>Long-term value: 700 mg/m³, 150 ppm<br>Long-term value: 700 mg/m³, 150 ppmTLV (USA)Long-term value: 700 mg/m³, 150 ppm<br>REL (USA)Long-term value: 700 mg/m³, 150 ppm<br>REL (USA)Cong-term value: 700 mg/m³, 150 ppm<br>REL (USA)Cong-term value: 700 mg/m³, 150 ppm<br>REL (USA)Cong-term value: 700 mg/m³, 150 ppmREL (USA)Long-term value: 713 mg/m³, 150 ppm   |                                       | hyl Propyl Ketone        |  |                       |  |
| TLV (USA)   Short-term value: 529 mg/m³, 150 ppm     1330-20-7 xylene (mix)     PEL (USA)   Long-term value: 435 mg/m³, 100 ppm     REL (USA)   Short-term value: 655 mg/m³, 150 ppm     Long-term value: 435 mg/m³, 100 ppm     TLV (USA)   Short-term value: 651 mg/m³, 100 ppm     TLV (USA)   Short-term value: 651 mg/m³, 100 ppm     Long-term value: 435 mg/m³, 100 ppm     Long-term value: 651 mg/m³, 100 ppm     BEI     108-65-6 PM acetate     WEEL (USA)   Long-term value: 50 ppm     110-19-0 isobutyl acetate     PEL (USA)   Long-term value: 700 mg/m³, 150 ppm     REL (USA)   Long-term value: 700 mg/m³, 150 ppm     REL (USA)   Long-term value: 700 mg/m³, 150 ppm     TLV (USA)   Long-term value: 713 mg/m³, 150 ppm   |                                       |                          |  |                       |  |
| 1330-20-7 xylene (mix)     PEL (USA)   Long-term value: 435 mg/m³, 100 ppm     REL (USA)   Short-term value: 655 mg/m³, 150 ppm     Long-term value: 435 mg/m³, 100 ppm   Short-term value: 651 mg/m³, 100 ppm     TLV (USA)   Short-term value: 651 mg/m³, 100 ppm     BEI   Long-term value: 434 mg/m³, 100 ppm     BEI   UOB-65-6 PM acetate     WEEL (USA)   Long-term value: 50 ppm     110-19-0 isobutyl acetate   PEL (USA)     PEL (USA)   Long-term value: 700 mg/m³, 150 ppm     REL (USA)   Long-term value: 700 mg/m³, 150 ppm     TLV (USA)   Long-term value: 713 mg/m³, 150 ppm  |                                       |                          |  |                       |  |
| PEL (USA)   Long-term value: 435 mg/m³, 100 ppm     REL (USA)   Short-term value: 655 mg/m³, 150 ppm     Long-term value: 435 mg/m³, 100 ppm     TLV (USA)   Short-term value: 651 mg/m³, 150 ppm     Long-term value: 434 mg/m³, 100 ppm     BEI <b>108-65-6 PM acetate</b> WEEL (USA)   Long-term value: 50 ppm <b>110-19-0 isobutyl acetate</b> PEL (USA)   Long-term value: 700 mg/m³, 150 ppm     REL (USA)   Long-term value: 700 mg/m³, 150 ppm     REL (USA)   Long-term value: 700 mg/m³, 150 ppm     TLV (USA)   Long-term value: 700 mg/m³, 150 ppm     REL (USA)   Long-term value: 700 mg/m³, 150 ppm     TLV (USA)   Long-term value: 700 mg/m³, 150 ppm  |                                       |                          | улт-, тоо ррпп   |                       |  |
| REL (USA)   Short-term value: 655 mg/m³, 150 ppm<br>Long-term value: 435 mg/m³, 100 ppm     TLV (USA)   Short-term value: 651 mg/m³, 150 ppm<br>Long-term value: 434 mg/m³, 100 ppm<br>BEI <b>108-65-6 PM acetate</b> WEEL (USA)   Long-term value: 50 ppm <b>110-19-0 isobutyl acetate</b> PEL (USA)   Long-term value: 700 mg/m³, 150 ppm     REL (USA)   Long-term value: 700 mg/m³, 150 ppm     TLV (USA)   Long-term value: 700 mg/m³, 150 ppm     REL (USA)   Long-term value: 700 mg/m³, 150 ppm     TLV (USA)   Long-term value: 713 mg/m³, 150 ppm   |                                       |                          | g/m <sup>3</sup> , 100 ppm   |                       |  |
| TLV (USA)   Short-term value: 651 mg/m³, 150 ppm<br>Long-term value: 434 mg/m³, 100 ppm<br>BEI <b>108-65-6 PM acetate</b> WEEL (USA)   Long-term value: 50 ppm <b>110-19-0 isobutyl acetate</b> PEL (USA)   Long-term value: 700 mg/m³, 150 ppm     REL (USA)   Long-term value: 700 mg/m³, 150 ppm     TLV (USA)   Long-term value: 700 mg/m³, 150 ppm     TLV (USA)   Long-term value: 713 mg/m³, 150 ppm   |                                       | Short-term value: 655 m  | a/m <sup>3</sup> , 150 ppm   |                       |  |
| Long-term value: 434 mg/m³, 100 ppm     BEI <b>108-65-6 PM acetate</b> WEEL (USA)     Long-term value: 50 ppm <b>110-19-0 isobutyl acetate</b> PEL (USA)     Long-term value: 700 mg/m³, 150 ppm     REL (USA)     Long-term value: 700 mg/m³, 150 ppm     TLV (USA)   Long-term value: 713 mg/m³, 150 ppm  |                                       |                          |  |                       |  |
| BEI     108-65-6 PM acetate     WEEL (USA)   Long-term value: 50 ppm     110-19-0 isobutyl acetate     PEL (USA)   Long-term value: 700 mg/m³, 150 ppm     REL (USA)   Long-term value: 700 mg/m³, 150 ppm     TLV (USA)   Long-term value: 713 mg/m³, 150 ppm  | ILV (USA)                             | Long-term value: 651 m   | g/m², 150 ppm<br>g/m³, 100 ppm   |                       |  |
| WEEL (USA)   Long-term value: 50 ppm     110-19-0 isobutyl acetate     PEL (USA)   Long-term value: 700 mg/m³, 150 ppm     REL (USA)   Long-term value: 700 mg/m³, 150 ppm     TLV (USA)   Long-term value: 713 mg/m³, 150 ppm  |                                       | BEI                      |  |                       |  |
| 110-19-0 isobutyl acetate     PEL (USA)   Long-term value: 700 mg/m³, 150 ppm     REL (USA)   Long-term value: 700 mg/m³, 150 ppm     TLV (USA)   Long-term value: 713 mg/m³, 150 ppm   |                                       |                          |  |                       |  |
| PEL (USA)Long-term value: 700 mg/m³, 150 ppmREL (USA)Long-term value: 700 mg/m³, 150 ppmTLV (USA)Long-term value: 713 mg/m³, 150 ppm  |                                       |                          | n  |                       |  |
| REL (USA)Long-term value: 700 mg/m³, 150 ppmTLV (USA)Long-term value: 713 mg/m³, 150 ppm  |                                       |                          | a/m³ 150 ppm   |                       |  |
| TLV (USA) Long-term value: 713 mg/m <sup>3</sup> , 150 ppm  |                                       |                          |  |                       |  |
|   |                                       |                          |  |                       |  |
|   | · · · · · · · · · · · · · · · · · · · |                          |  | (Contd. on page 3)    |  |

Revised On 02/02/2015

Page 3/5

| Γ GREEN   |
|---|
| (Contd. of page 2)  |
| values:   |
|   |
| onspecific)   |
|   |
|   |
|   |
| uric acids  |
| Keep away from foodstuffs and animal feed. Wash hands after use.<br>Immediately remove all soiled and contaminated clothing.<br>Wash hands after use.<br>Avoid contact with the eyes and skin.<br>Do not eat or drink while working.<br>A respirator is generally not necessary when using this product outdoors or in large open areas.<br>In cases where short and/or long term overexposure exists, a charcoal filter respirator should be |
| In cases where short and/or long term overexposure exists, a charcoal filter respirator should be<br>worn. If you suspect overexposure conditions exist, please consult an authority on chemical<br>hygeine.<br>Protective gloves. The glove material must be impermeable and resistant to the substance.<br>Tightly sealed goggles   |
| ties  |
| Aerosol.<br>Aromatic<br>Not determined.   |
|   |

| Appearance:<br>Odor:<br>Odor threshold:   | Aerosol.<br>Aromatic<br>Not determined.   |
|---|---|
| pH-value:<br>Melting point/Melting range<br>Boiling point:  | Not determined.<br>Undetermined.<br>-44 °C (-47 °F)   |
| Flash point:<br>Flammability (solid, gas):  | -19 °C (-2 °F)<br>Extremely flammable.  |
| Decomposition temperature:  | Not determined.   |
| Auto igniting:  | Product is not self-igniting.   |
| Danger of explosion:<br>Lower Explosion Limit:<br>Upper Explosion Limit:  | In use, may form flammable/explosive vapour-air mixture.<br>1.7 Vol %<br>10.9 Vol %                                   |
| Vapor pressure:<br>Relative Density:<br>Vapour density<br>Evaporation rate<br>Partition coefficient: n-octonal/water: | Not determined.<br>Between 0.77 and 0.85 (Water equals 1.00)<br>Not determined.<br>Not applicable.<br>Not determined. |
| Solubility:<br>Viscosity:   | Not determined.<br>Not determined.  |
| VOC content:<br>VOC content (less exempt solvents):<br>MIR Value:   | 507.0 g/l / 4.23 lb/gl<br>49.2 %<br>1.12  |
| Solids content:   | 31.9 %  |

| 10 Stability and reactivity   |  |                                 |
|---|--|---------------------------------|
| Reactivity:<br>Conditions to avoid:   | Stable at normal temperatures.<br>Do not allow can to exceed 120 degrees Fahrenheit.<br>temperatures.  | Do not warehouse in subfreezing |
| Chemical stability:<br>Possibility of hazardous reactions:<br>Incompatible materials:<br>Hazardous decomposition: | Not <sup>*</sup> fully evaluated.<br>No dangerous reactions known.<br>No further relevant information available.<br>No dangerous decomposition products known. |                                 |

| 11 Toxicolo | 11 Toxicological information                         |                     |                   |
|-------------|--|---------------------|-------------------|
| LD/LC50     | LD/LC50 values that are relevant for classification: |                     |                   |
|             | 106-97-8 n-butane                                    |                     |                   |
| Inhalative  | Inhalative LC50/4 h 658 mg/l (rat)                   |                     |                   |
| 108-10-1    | 108-10-1 methyl isobutyl ketone                      |                     |                   |
| Oral        | LD50   | 2100 mg/kg (rat)    |                   |
| Dermal      | LD50   | 16000 mg/kg (rab)   |                   |
| Inhalative  | LC50/4 h   | 8.3-16.6 mg/l (rat) |                   |
|             | •  | (                   | Contd. on page 4) |

L

L

Revised On 02/02/2015

Page 4/5

| Trade name: NEW FARM & IMPLEMENT GR                       | REEN  |  |
|---|---|--|
|   | (Contd. of pa   | ige 3)                                       |
| 1330-20-7 xylene (mix)                                    |   |  |
| Oral LD50 8700 mg/kg (rat)                                |   |  |
| Dermal LD50 2000 mg/kg (rbt)                              |   |  |
| Inhalative LC50/4 h 6350 mg/l (rat)                       |   |  |
| 108-65-6 PM acetate                                       |   |  |
| Oral LD50 8500 mg/kg (rat)                                |   |  |
| Inhalative LC50/4 h 35.7 mg/l (rat)                       |   |  |
| 110-19-0 isobutyl acetate                                 |   |  |
| Oral LD50 4763 mg/kg (rbt)                                |   |  |
| Information on toxicological effects:                     |   |  |
| Skin effects:   | No irritant effect.   |  |
| Eve effects:  | Irritating effect.  |  |
| Sensitization:  | No sensitizing effects known.   |  |
| Carcinogenic categories                                   |   |  |
| IARC (International Agency for Rese                       | arch on Cancor  |  |
| 108-10-1 methyl isobutyl ketone                           |   | 2B   |
|   |   |  |
| 1330-20-7 xylene (mix)                                    |   | 3  |
| NTP (National Toxicology Program)                         |   |  |
| None of the ingredients is listed.                        |   |  |
|   |   |  |
| 40 Feeleniest information                                 |   |  |
| 12 Ecological information                                 |   |  |
| Aquatic toxicity:   | Hazardous for water, do not empty into drains.  |  |
| Persistence and degradability:                            | The product is degradable after prolonged exposure to natural weathering processes.             |  |
| Bioaccumulative potential:                                | No further relevant information available.  |  |
| Mobility in soil:<br>Other adverse effects:               | No further relevant information available.<br>No further relevant information available.        |  |
|   |   |  |
|   |   |  |
| 13 Disposal considerations                                |   |  |
| Dispose of in accordance with local, s                    | state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans r | nust   |
| be disposed of responsibly. Do not hea                    | at or cut empty containers with electric or gas torches.  |  |
| Recommendation:   | Completely empty cans should be recycled.   |  |
|   |   |  |
| 14 Transport information                                  |   |  |
| -   |   |  |
| UN-Number   | UN1950  |  |
| DOT   | N/A<br>UN1950   |  |
| DOT   | Consumer Commodity ORM-D  |  |
| DOI   | Aerosols, flammable   |  |
| ADR   | 1950 Aerosols   |  |
| Transport hazard class(es):                               |   |  |
| Class   | 2.1   |  |
| Marine pollutant:   | No  |  |
| Special precautions for user:                             | Warning: Gases  |  |
| EMS Number:   | F-D,S-Ŭ   |  |
| Packaging Group:  |   |  |
| UN "Model Regulation":                                    | UN1950, Aerosols, 2.1   |  |
|   |   |  |
| 15 Regulatory information                                 |   |  |
| SARA Section 355 (extremely hazard                        | doue substances).   | _  |
| None of the ingredients in this product                   |   |  |
|   |   |  |
| SARA Section 313 (Specific toxic ch                       | nemical listings):  |  |
| 7727-43-7 barium sulfate, natural                         |   |  |
| 108-10-1 methyl isobutyl ketone                           |   |  |
| 1330-20-7 xylene (mix)                                    |   |  |
| CPSC:   | This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.           |  |
| California Proposition 65 chemicals                       |   |  |
| 108-10-1 methyl isobutyl ketone                           |   |  |
| 13463-67-7 titanium dioxide                               |   |  |
|   |   |  |
| 100-41-4 ethyl benzene                                    |   |  |
| 1333-86-4 Carbon black                                    |   |  |
| CANADIAN ENVIRONMENTAL                                    |   |  |
| PROTECTION ACT:   | All hazardous ingredients for this product appear on the Canadian Domestice Substance List      | <u>.                                    </u> |
| EPA:  |   |  |
| 67-64-1 Acetone   |   |  |
| 7727-43-7 barium sulfate, natural                         | D, CBD(inh), NL(or  | ral)   |
|   |   | ,  |
| 108-10-1 methyl isobutyl ketone                           |   |  |
| 108-10-1 methyl isobutyl ketone                           |   |  |
| 108-10-1 methyl isobutyl ketone<br>1330-20-7 xylene (mix) | I<br>I<br>(Contribution pro-  | ae 5)  |
|   | I<br>I<br>(Contd. on pa   | ıge 5)                                       |
|   | I<br>I<br>(Contd. on pa   | ige 5)                                       |

Revised On 02/02/2015

Page 5/5

110-19-0 isobutyl acetate

**16 Other information** 

Contact: Date of preparation / last revision Regulatory Affairs 04/15/2015 / - (Contd. of page 4)