Safety Data Sheet

Page 1/5

Printing date 04/16/2015	Revised On 02/02/20	15	
1 Identification of the substance and manufacturer			
Trade name:	IHC RED		
Product code:			
IBS Part Number	81441		
Product category	PC9a Paints and coatings.		
Manufacturer/Supplier:	Seymour of Sycamore		
	917 Crosby Avenue, Sycamore, IL 60178		
Emergency telephone number:	Phone: 815-895-9101 www.seymourpaint.com CHEMTEL 1-800-255-3924, or 813-248-0585.		
Emergency telephone number.	CHEMITEE 1-800-235-3924, 01 813-248-0365.		
2 Hazard(s) identification			
Classification of the substance or m			
Flam. Aerosol 1 H222 Extremely flam			
	nder pressure; may explode if heated.		
Carc. 2 H351 Suspected of c			
	nage to organs through prolonged or repeated exposure.		
Eye Irrit. 2A H319 Causes serious			
STOT SE 3 H336 May cause drov	wsiness or dizziness.		
GHS Hazard pictograms			
	$\bigvee \bigvee \bigvee \bigvee \bigvee$		
	GHS02 GHS04 GHS07 GHS08		
Signal word	Danger		
Hazard statements	Extremely flammable aerosol.		
	Contains gas under pressure; may explode if heated.		
	Causes serious eye irritation.		
	Suspected of causing cancer. May cause drowsiness or dizziness.		
	May cause drowsiness of dizziness. May cause damage to organs through prolonged or repeated exposure.		
Precautionary statements	If medical advice is needed, have product container or label at hand.		
	Keep out of reach of children.		
	Read label before use.		
	Obtain special instructions before use. Keep away from heat/sparks/open flames/hot surfaces No smoking.		
	Do not spray on an open flame or other ignition source.		
	Pressurized container: Do not pierce or burn, even after use.		
	Wash hands thoroughly after handling.		
	Use only outdoors of in a well-ventilated area.		
	Wear protective gloves/protective clothing/eye protection/face protection. Do not handle until all safety precautions have been read and understood.		
	Do not breathe dust/fume/gas/mist/vapors/spray.		
	IF INHALED: Remove person to fresh air and keep comfortable for breathing.		
	If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if prese and easy to do. Continue rinsing.	nı	
	Call a poison center/doctor if you feel unwell.		
	If eye irritation persists: Get medical advice/attention.		
	Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.		
	Store in a well-ventilated place. Keep container tightly closed.		
	Dispose of contents/container in accordance with local/regional/national/internation	al	
	regulations.		
3 Composition/information on ingre- Chemical characterization: Mixtures	equents		
Chemical Description:	This product is a mixture of the substances listed below with nonhazardous additions.		
Dangerous components:			
67-64-1 Acetone	19.1%		
74-98-6 propane	15.77%		
106-97-8 n-butane	9.26%		
7727-43-7 barium sulfate, natural	8.05%		
108-10-1 methyl isobutyl ketone	5.22%		
2807-30-9 Glycol Ether EP	5.15%		
108-65-6 PM acetate	3.25%		
107-87-9 Methyl Propyl Ketone	2.67%		
1330-20-7 xylene (mix)	2.34%		
110-19-0 isobutyl acetate	1.5%		
64742-94-5 Solvent naphtha, heavy ar			
,,,,,,,			

4 First-aid measures	
After inhalation: After skin contact:	Supply fresh air; consult doctor in case of complaints. Remove contaminated clothing. Wash exposed area with soap and water.
After eye contact:	Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
After swallowing:	Rinse out mouth and then drink plenty of water. Rinse mouth with water. Do not induce vomiting.
	(Contd. on page 2)

Safety Data Sheet

Page 2/5

Printing date 04/16/201	5		Revised On 02/02/2015
Trade name: IHC	RED		
Most importa	ant symptoms and		(Contd. of page 1)
effects:		Dizziness	
attention nee	any immediate medical	No further relevant information available.	
5 Fire-fighting	g measures		
Extinguishin	g agents:	CO2, extinguishing powder or water spray. Fight larger fires with water spray.	
Special haza Protective eq	ras: Juipment for	Can form explosive gas-air mixtures.	
firefighters:	• •	A respiratory protective device may be necessary.	
	release measures		
	cautions, protective nd emergency		
procedures:		Wear protective equipment. Keep unprotected persons away.	
Methods and	material for	Use respiratory protective device against the effects of fumes/dust/aerosol.	
	and cleaning up:	Ensure adequate ventilation.	
7 Handling an	-	Lies only in well ventileted erace	
Storage requ	for safe handling iirements:	Use only in well ventilated areas. Keep away from sources of heat and direct sunlight. Do not warehou	se in subfreezing
		conditions. Store locked up.	
	ontrols/personal prote		
67-64-1 Aceto		equire monitoring at the workplace:	
PEL (USA)	Long-term value: 2400 m	ng/m³, 1000 ppm	
REL (USA)	Long-term value: 590 mg		
TLV (USA)	Short-term value: (1782)	NIC-1187 mg/m <sup>3</sup> , (750) NIC-500 ppm	
	Long-term value: (1188) BEI	NIC-594 mg/m³, (500) NIC-250 ppm	
74-98-6 propa			
PEL (USA)	Long-term value: 1800 m		
REL (USA) TLV (USA)	Long-term value: 1800 m refer to Appendix F	ng/m³, 1000 ppm	
106-97-8 n-bi			
REL (USA)	Long-term value: 1900 m		
TLV (USA)	Short-term value: 2370 n	ng/m³, 1000 ppm	
PEL (USA)	rium sulfate, natural Long-term value: 15* 5**	mg/m <sup>3</sup>	
1 22 (00,1)	*total dust **respirable fr	action	
REL (USA)	Long-term value: 10* 5** *total dust **respirable fra	mg/m <sup>3</sup>	
TLV (USA)	Long-term value: 5* mg/i		
, , ,	*inhalable fraction; E		
108-10-1 met PEL (USA)	hyl isobutyl ketone Long-term value: 410 mg	1/m3 100 ppm	
REL (USA)	Short-term value: 300 m	g/m³, 75 ppm	
	Long-term value: 205 mg	j/m³, 50 ppm	
TLV (USA)	Short-term value: 307 m Long-term value: 82 mg/	g/m³, /5 ppm m³, 20 ppm	
	BEI		
108-65-6 PM			
	Long-term value: 50 ppm hyl Propyl Ketone	1	
PEL (USA)	Long-term value: 700 mg	y/m³, 200 ppm	
REL (USA)	Long-term value: 530 mg	ŋ/m³, 150 ppm	
TLV (USA) 1330-20-7 xyl	Short-term value: 529 mg	g/m³, 150 ppm	
PEL (USA)	Long-term value: 435 mg	n/m <sup>3</sup> , 100 ppm	
REL (USA)	Short-term value: 655 m	g/m <sup>3</sup> , 150 ppm	
	Long-term value: 435 mg Short-term value: 651 mg		
TLV (USA)	Long-term value: 434 mg	g/m <sup>3</sup> , 100 ppm	
440.40.01	BEI		
110-19-0 isot PEL (USA)	Long-term value: 700 mg	1/m³ 150 ppm	
REL (USA)	Long-term value: 700 mg		
TLV (USA)	Long-term value: 713 mg		
			(Contd. on page 3)

Revised On 02/02/2015

Page 3/5

## **Trade name: IHC RED**

	(Contd. of page 2)
Ingredients with biological limit v	alues:
67-64-1 Acetone	
BEI (USA) 50 mg/L Medium: urine Time: end of shift	
Parameter: Acetone (no	nspecific)
108-10-1 methyl isobutyl ketone	
BEI (USA) 1 mg/L Medium: urine Time: end of shift Parameter: MIBK	
1330-20-7 xylene (mix)	
BEI (USA) 1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippu	ric acids
Hygienic protection:	Keep away from foodstuffs and animal feed. Wash hands after use. Immediately remove all soiled and contaminated clothing. Wash hands after use. Avoid contact with the eyes and skin. Do not eat or drink while working.
Breathing equipment:	A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygeine.
Hand protection: Eye protection:	Protective gloves. The glove material must be impermeable and resistant to the substance. Tightly sealed goggles

9 Physical and chemical properties		
Appearance:	Aerosol.	
Odor:	Aromatic	
Odor threshold:	Not determined.	
pH-value:	Not determined.	
Melting point/Melting range	Undetermined.	
Boiling point:	-44 °C (-47 °F)	
Flash point:	-19 °C (-2 °F)	
Flammability (solid, gas):	Extremely flammable.	
Decomposition temperature:	Not determined.	
Auto igniting:	Product is not self-igniting.	
Danger of explosion:	In use, may form flammable/explosive vapour-air mixture.	
Lower Explosion Limit:	1.7 Vol %	
Upper Explosion Limit:	10.9 Vol %	
Vapor pressure:	Not determined.	
Relative Density:	Between 0.77 and 0.85 (Water equals 1.00)	
Vapour density	Not determined.	
Evaporation rate	Not applicable.	
Partition coefficient: n-octonal/water:	Not determined.	
Solubility:	Not determined.	
Viscosity:	Not determined.	
VOC content:	494.7 g/l / 4.13 lb/gl	
VOC content (less exempt solvents):	47.8 %	
MIR Value:	1.18	
Solids content:	32.5 %	

## **10 Stability and reactivity** Reactivity: Conditions to avoid: Stable at normal temperatures. Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing temperatures. Chemical stability: Possibility of hazardous reactions: Incompatible materials: Hazardous decomposition: Not fully evaluated. No dangerous reactions known. No further relevant information available. No dangerous decomposition products known.

<b>11 Toxicolo</b>	gical info	prmation	
LD/LC50	values tha	t are relevant for classification:	
106-97-8 ı	n-butane		
Inhalative	LC50/4 h	658 mg/l (rat)	
108-10-1 ı	108-10-1 methyl isobutyl ketone		
Oral	LD50	2100 mg/kg (rat)	
Dermal	LD50	16000 mg/kg (rab)	
Inhalative	LC50/4 h	8.3-16.6 mg/l (rat)	
		(Contd. on page 4)	

(Contd. on page 4)

Page 4/5

Revised On 02/02/2015

		Revised On 02/02/2015
Trade name: IHC RED		
		(Contd. of page 3)
108-65-6 PM acetate		
Oral LD50 8500 mg/kg (ra	it)	
Inhalative LC50/4 h 35.7 mg/l (rat)		
1330-20-7 xylene (mix)	.0	
Oral LD50 8700 mg/kg (ra		
Dermal LD50 2000 mg/kg (rb		
Inhalative LC50/4 h 6350 mg/l (rat)		
110-19-0 isobutyl acetate		
Oral LD50 4763 mg/kg (rb		
Information on toxicological effec Skin effects:	ts: No data available. No irritant effect.	
Eye effects:	Irritating effect.	
Sensitization:	No sensitizing effects known.	
Carcinogenic categories	5	
IARC (International Agency for Re	search on Cancer)	
108-10-1 methyl isobutyl ketone	Search on Cancer	2B
1330-20-7 xylene (mix)		3
		<u> </u>
NTP (National Toxicology Program	nj	
None of the ingredients is listed.		
12 Ecological information		
Aquatic toxicity:	Hazardous for water, do not empty into drains.	
Persistence and degradability:	The product is degradable after prolonged exposure to natural weatherin	g processes.
Bioaccumulative potential:	No further relevant information available.	
Mobility in soil:	No further relevant information available.	
Other adverse effects:	No further relevant information available.	
13 Disposal considerations		
Dispose of in accordance with local	, state, and federal regulations. Do not puncture, incinerate, or compact. P	artially empty cans must
be disposed of responsibly. Do not r Recommendation:	eat or cut empty containers with electric or gas torches. Completely empty cans should be recycled.	
Recommendation:	Completely empty cans should be recycled.	
14 Transport information		
UN-Number	UN1950	
DOT		
DOT	Consumer Commodity ORM-D Aerosols, flammable	
ADR	1950 Aerosols	
Transport hazard class(es):		
Class	2.1	
Marine pollutant: Special precautions for user:	No Warning: Casaa	
EMS Number:	Warning: Gases F-D,S-U	
Packaging Group:		
UN "Model Regulation":	UN1950, Aerosols, 2.1	
15 Regulatory information		
SARA Section 355 (extremely haza	ardous substances):	
None of the ingredients in this produ		
SARA Section 313 (Specific toxic	chemical listings):	
7727-43-7 barium sulfate, natural		
108-10-1 methyl isobutyl ketone		
1330-20-7 xylene (mix)		- 00 mmm - f  !
CPSC:	This product complies with 16 CFR 1303 and does not contain more that	n an bhu or leag.
California Proposition 65 chemica	is known to cause cancer:	
108-10-1 methyl isobutyl ketone		
13463-67-7 titanium dioxide		
100-41-4 ethyl benzene		
CANADIAN ENVIRONMENTAL PROTECTION ACT:	All bazardous ingradiants for this product appear on the Canadian Dama	etico Substance List
EPA:	All hazardous ingredients for this product appear on the Canadian Dome	
67-64-1 Acetone		
7727-43-7 barium sulfate, natural		D CBD(inb) NII (aral)
		D, CBD(inh), NL(oral)
108-10-1 methyl isobutyl ketone 1330-20-7 xylene (mix)		
110-19-0 isobutyl acetate		D
16 Other information		
Contact:	Regulatory Affairs	
Contact.	0 5	
oomaat.	5	(Contd. on page 5)

(Contd. of page 4)

Page 5/5

Date of preparation / last revision 04/16/2015 / -