

LOCK ON TO SAVINGS

SAVE TIME — SAVE GREASE — SAVE MONEY!

LOCK-N-LUBE GREASE COUPLERS

AVAILABLE IN L & XL SIZES

IBS No. 5855 – L

IBS No. 5856 – XL



The Lock-N-Lube Grease Coupler has been a popular item and is now available in the Lock-N-Lube XL – the same features as the standard, but with a longer barrel – 3.6" of effective reach. Perfect for greasing U-joints, harvester heads, shielded PTO shafts, and deeply recessed zerks.

- **Unique sliding sleeve**, activated by a thumb lever – locks the four spring steel jaw in place.
- **Leak-proof seal** – No hands needed to align or hold the coupler in place while greasing.
- **Works with all grease gun types**: pneumatic, manual and electric.
- Works on all DIN & SAE Zerks.
- Fits 1/8" NPT thread
- **No need to align or hold the coupler** while greasing: Lock on and free up both hands - to operate the grease gun - depress trigger to release.
- **Durable nitrile rubber seal** for longevity under high pressure.
- **Four hardened spring steel jaws** are resilient under high pressure.
- **Check valve** to reduce leakage.



HANDS-FREE, LEAK-FREE GREASING IS A REALITY

LOCK-N-LUBE - L
NOW ONLY

\$29⁹⁵!

IBS No. 5855



LOCK-N-LUBE - XL
NOW ONLY

\$39⁹⁵!


IBS No. 5856

LOCK-N-FLATE AIR CHUCK INFLATION IS A VACATION!

SECURE + HANDS-FREE + LEAK-FREE

- **REVOLUTIONARY DESIGN**
six steel jaws lock onto any Schrader valve to create a secure, hands free connection.
- **1/4" NPT THREAD SIZE**
compatible with most standard air hoses.
- **HARDENED STEEL COLLET**
Fits ALL standard Schrader valves (VG8/8V1 valve threads).
- **RATED TO 150 PSI**
Suitable for garage & Industrial systems, auto and manual tire inflators, portable pressure gauges & constant pressure systems.
- **HEAVY DUTY CONSTRUCTION**
is built to last and stand up to everyday use even in the busiest tire shops, service bays and garages.
- **SPRING LOADED TPU SEAL**
Inflates tires with or without the core valve in place.

NOW ONLY ~~\$39.99~~!



DEPRESS THE THUMB LEVER & PUSH ON THE TIRE VALVE, RELEASE THE LEVER TO SECURE THE AIR CHUCK & CREATE A LEAK-FREE CONNECTION!

IBS No. 5858



HARDENED STEEL COLLET FITS ALL SHRADER VALVES RATED TO 150 PSI

SLIDING SLEEVE SECURELY LOCKS THE AIR CHUCK ONTO THE SHRADER VALVE

INFLATE DUAL TIRES EASY

DUAL WHEEL LOCKING AIR CHUCK IBS No. 5859

Two-jaw locking design with a patented remote actuator.

Extended reach to securely inflate duals.


Easily disconnect with the actuator. No need to reach in to disconnect.

Best for airing up inner wheels on semis and other large trucks.

- Fixed Head won't swivel or move when trying to attach.
- Long Reach for easier access to second wheels and harder to reach areas.
- Blue Silicone Grip for better ergonomics and hold.
- Standard 1/4" FNPT thread for easy connection to air lines
- Overall Length: 15.5 in. (40 cm.)
- Maximum pressure: 150 PSI (10.3 BAR)

HOW TO USE: Pull the blue actuator collar back towards you to release the front jaws and push the collar away from you to release the rear jaws.

ONLY \$99⁹⁹!



The Dual Locking Head allows you to push onto valves facing towards you, or pull onto valves facing away from you.

