

## Safety Data Sheet

Printing date 01/24/2024

Revised On 01/24/2024

## 1 Identification of the substance and manufacturer

**Trade name:** DRY GRAPHITE LUBE  
**Product code:** 74125  
**Recommended use:** Paint and coatings application.  
**Uses advised against:** Any that differs from the recommended use.  
**Manufacturer/Supplier:** IBS, Inc.  
 740 Clay St NW, Auburn, WA 98001  
 253-804-8666 www.industrialbolt.com  
**Emergency telephone number:** 1-800-255-3924 VELOCITY EHS



**IBS, Inc.**  
 SPECIALTY PRODUCTS FOR MAINTENANCE & REPAIR  
**INDUSTRIALBOLT.COM • 800-678-1906**

## 2 Hazard(s) identification

## Classification of the substance or mixture

Flammable Aerosols 1 H222 Extremely flammable aerosol.  
 Gases under Pressure - Liquefied gas H280 Contains gas under pressure; may explode if heated.  
 Eye Irritation 2A H319 Causes serious eye irritation.  
 Toxic to Reproduction 1B H360 May damage fertility or the unborn child.  
 Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness.  
 Specific Target Organ Toxicity - Repeated Exposure 2 H373 May cause damage to organs through prolonged or repeated exposure.

Checked: 01/19/2026

Additional information:  
GHS Hazard pictograms

GHS02 GHS04 GHS07 GHS08

Signal word  
Hazard statements

Danger  
 Extremely flammable aerosol.  
 Contains gas under pressure; may explode if heated.  
 Causes serious eye irritation.  
 May damage fertility or the unborn child.  
 May cause drowsiness or dizziness.  
 May cause damage to organs through prolonged or repeated exposure.  
**Precautionary statements**  
 Obtain special instructions before use.  
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
 Do not spray on an open flame or other ignition source.  
 Pressurized container: Do not pierce or burn, even after use.  
 Do not breathe dust/fume/gas/mist/vapors/spray.  
 Wash thoroughly after handling.  
 Use only outdoors or in a well-ventilated area.  
 Wear protective gloves/protective clothing/eye protection/face protection.  
 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 Call a poison center/doctor if you feel unwell.  
 If eye irritation persists: Get medical advice/attention.  
 Store in a well-ventilated place.  
 Store locked up.  
 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.  
 Dispose of contents/container in accordance with local/regional/national/international regulations.

## 3 Composition/information on ingredients

## Chemical characterization: Mixtures

**Chemical Description:** This product is a mixture of the substances listed below with nonhazardous additions.

## Dangerous components:

67-64-1	Acetone	25-50%
74-98-6	propane	15-25%
67-63-0	Isopropyl Alcohol	10-15%
106-97-8	n-butane	10-15%
108-88-3	Toluene	1-5%

## 4 First-aid measures

**After inhalation:** Supply fresh air; consult doctor in case of complaints.  
**After skin contact:** Remove contaminated clothing. Wash exposed area with soap and water.  
**After eye contact:** Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.  
**After swallowing:** Rinse out mouth and then drink plenty of water.  
 Rinse mouth with water. Do not induce vomiting.  
**Most important symptoms and effects:** Dizziness

(Contd. on page 2)

## Safety Data Sheet

Printing date 01/24/2024

Revised On 01/24/2024

Trade name: DRY GRAPHITE LUBE

(Contd. of page 1)

**Indication of any immediate medical attention needed:** No further relevant information available.

**5 Fire-fighting measures**

**Extinguishing agents:** CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray.  
**Special hazards:** Can form explosive gas-air mixtures.  
**Protective equipment for firefighters:** A respiratory protective device may be necessary.

**6 Accidental release measures**

**Personal precautions, protective equipment and emergency procedures:** Wear protective equipment. Keep unprotected persons away.  
Use respiratory protective device against the effects of fumes/dust/aerosol.  
**Methods and material for containment and cleaning up:** Ensure adequate ventilation.  
Dispose contaminated material as waste according to section 13.

**7 Handling and storage**

**Precautions for safe handling** Use only in well ventilated areas.  
**Storage requirements:** Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions.  
Store locked up.

**8 Exposure controls/personal protection****Components with limit values that require monitoring at the workplace:****67-64-1 Acetone**

PEL (USA) Long-term value: 2400 mg/m<sup>3</sup>, 1000 ppm  
REL (USA) Long-term value: 590 mg/m<sup>3</sup>, 250 ppm  
TLV (USA) Short-term value: 500 ppm  
Long-term value: 250 ppm  
A4, BEI

**74-98-6 propane**

PEL (USA) Long-term value: 1800 mg/m<sup>3</sup>, 1000 ppm  
REL (USA) Long-term value: 1800 mg/m<sup>3</sup>, 1000 ppm  
TLV (USA) see Appendix F Minimal oxygen content ( D, EX)

**67-63-0 Isopropyl Alcohol**

PEL (USA) Long-term value: 980 mg/m<sup>3</sup>, 400 ppm  
REL (USA) Short-term value: 1225 mg/m<sup>3</sup>, 500 ppm  
Long-term value: 980 mg/m<sup>3</sup>, 400 ppm  
TLV (USA) Short-term value: 400 ppm  
Long-term value: 200 ppm  
BEI, A4

**106-97-8 n-butane**

REL (USA) Long-term value: 1900 mg/m<sup>3</sup>, 800 ppm  
TLV (USA) Short-term value: 1000 ppm  
(EX)

**108-88-3 Toluene**

PEL (USA) Long-term value: 200 ppm  
Ceiling limit value: 300; 500\* ppm  
\*10-min peak per 8-hr shift  
REL (USA) Short-term value: 560 mg/m<sup>3</sup>, 150 ppm  
Long-term value: 375 mg/m<sup>3</sup>, 100 ppm  
TLV (USA) Long-term value: 20 ppm  
BEI, OTO, A4

**107-98-2 Glycol ether PM**

REL (USA) Short-term value: 540 mg/m<sup>3</sup>, 150 ppm  
Long-term value: 360 mg/m<sup>3</sup>, 100 ppm  
TLV (USA) Short-term value: 100 ppm  
Long-term value: 50 ppm  
A4

(Contd. on page 3)

## Safety Data Sheet

Printing date 01/24/2024

Revised On 01/24/2024

Trade name: DRY GRAPHITE LUBE

(Contd. of page 2)

**Ingredients with biological limit values:****67-64-1 Acetone**

BEI (USA) 25 mg/L  
 Medium: urine  
 Time: end of shift  
 Parameter: Acetone (nonspecific)

**67-63-0 Isopropyl Alcohol**

BEI (USA) 40 mg/L  
 Medium: urine  
 Time: end of shift at end of workweek  
 Parameter: Acetone (background, nonspecific)

**108-88-3 Toluene**

BEI (USA) 0.02 mg/L  
 Medium: blood  
 Time: prior to last shift of workweek  
 Parameter: Toluene

0.03 mg/L  
 Medium: urine  
 Time: end of shift  
 Parameter: Toluene

0.3 mg/g creatinine  
 Medium: urine  
 Time: end of shift  
 Parameter: o-Cresol with hydrolysis (background)

**Hygienic protection:**

Keep away from foodstuffs and animal feed. Wash hands after use.  
 Immediately remove all soiled and contaminated clothing.  
 Wash hands after use.  
 Store protective clothing separately.  
 Avoid contact with the eyes and skin.  
 Do not eat or drink while working.

**Breathing equipment:**

A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a NIOSH approved respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygiene.

**Hand protection:**

Nitrile gloves.  
 The glove material must be impermeable and resistant to the substance.

**Eye protection:**

Tightly sealed goggles

**9 Physical and chemical properties**

**Appearance:** Aerosol.  
**Odor:** Aromatic  
**Odor threshold:** Not determined.  
**pH-value:** Not determined.  
**Melting point/Melting range:** Undetermined.  
**Boiling point:** -44 °C (-47.2 °F)  
**Flash point:** -20 °C (-4 °F)  
**Flammability (solid, gas):** Extremely flammable.  
**Decomposition temperature:** Not determined.  
**Auto igniting:** Product is not self-igniting.  
**Danger of explosion:** In use, may form flammable/explosive vapour-air mixture.  
**Lower Explosion Limit:** 1.7 Vol %  
**Upper Explosion Limit:** 12 Vol %  
**Vapor pressure:** Not determined.  
**Relative Density:** Between 0.77 and 0.85 (Water equals 1.00)  
**Vapor density:** Not determined.  
**Evaporation rate:** Not applicable.  
**Partition coefficient: n-octanol/water:** Not determined.  
**Solubility:** Not determined.  
**Viscosity:** Not determined.

**10 Stability and reactivity**

**Reactivity:** Stable at normal temperatures.  
**Conditions to avoid:** Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing temperatures.  
**Chemical stability:** Not fully evaluated.  
**Possibility of hazardous reactions:** No dangerous reactions known.

(Contd. on page 4)

## Safety Data Sheet

Printing date 01/24/2024

Revised On 01/24/2024

Trade name: DRY GRAPHITE LUBE

**Incompatible materials:** No further relevant information available.  
**Hazardous decomposition:** No dangerous decomposition products known.

(Contd. of page 3)

## 11 Toxicological information

## LD/LC50 values that are relevant for classification:

## 67-63-0 Isopropyl Alcohol

Oral	LD50	4,570 mg/kg (rat)
Dermal	LD50	13,400 mg/kg (rab)
Inhalative	LC50/4 h	30 mg/l (rat)

## 107-98-2 Glycol ether PM

Oral	LD50	5,000 mg/kg (rat)
Dermal	LD50	13,500 mg/kg (rbt)
Inhalative	LC50/4 h	6 mg/l (rat)

**Information on toxicological effects:** No data available.  
**Skin effects:** No irritant effect.  
**Eye effects:** Irritating effect.  
**Sensitization:** No sensitizing effects known.

## 12 Ecological information

**Aquatic toxicity:** Hazardous for water, do not empty into drains.  
**Persistence and degradability:** The product is degradable after prolonged exposure to natural weathering processes.  
**Other information:** This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), or chlorinated solvents.  
**Bioaccumulative potential:** No further relevant information available.  
**Mobility in soil:** No further relevant information available.  
**Other adverse effects:** No further relevant information available.

## 13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.  
**Recommendation:** Completely empty cans should be recycled.  
**Recommended cleansing agent:** Water, if necessary with cleansing agents.

## 14 Transport information

**UN-Number:** UN1950  
**DOT:** UN1950  
**ADR:** UN1950  
**DOT:** Aerosols, flammable  
**ADR:** 1950 Aerosols  
**Transport hazard class(es):** ID8000 Consumer Commodity Class 9  
**Class:** 2.1 Gases  
**Marine pollutant:** No  
**Special precautions for user:** Warning: Gases  
**EMS Number:** F-D,S-U  
**Packaging Group:** --  
**UN "Model Regulation":** UN1950, Aerosols, 2.1

## 15 Regulatory information

## SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed.

## SARA Section 313 (Specific toxic chemical listings):

67-63-0	Isopropyl Alcohol
108-88-3	Toluene

**Toxic Substances Control Act (TSCA):** All hazardous ingredients are found on the inventory list of substances.  
**Canadian Domestic Substances List (DSL):** All ingredients are listed or exempted.  
**Consumer Product Safety Commission (CPSC):** This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

## California Proposition 65 chemicals known to cause cancer:

None of the ingredients in this product are listed.

## Prop 65 chemicals known to cause birth defects or reproductive harm:

108-88-3	Toluene
----------	---------

(Contd. on page 5)

# Safety Data Sheet

Printing date 01/24/2024

Revised On 01/24/2024

**Trade name:** DRY GRAPHITE LUBE

(Contd. of page 4)

**EPA:**

67-64-1 | Acetone

## 16 Other information

**Contact:** Regulatory Affairs